





QView QPC80 Portable Document Camera HDMI Input / Output



Flexible Gooseneck





QView QPC80 Portable Document Camera

5.0 Megapixel		Flexible boseneck	Save Images & Video
ltem	QPC80	¥1	
Resolution	XGA, SXGA, WXGA, 720p, 1080p		
Total Pixels	5MP		
Zoom	5x Optical Zoom 10x Electrical Zoom		
Camera Rotation	Free (Gooseneck)		
Focus	Auto / Manual	Flexible	
White balance	Auto	Gooseneck	
Imagine Features	Neg/Pos, Black/White, Split, Title, Freeze, Rotate, Save & Recall	to twist to many angles	
Image Rotate	0° 90° 180° 270°	· •	\backslash
Image Save & Recall	50 frames saved in flash ROM		Bubble
Image Transfer	SD Card		
Lights	2W LED Lamps		Level
Input connectors	HDMI, VGA, PC Audio, Mic In		
Output connectors	HDMI, VGA, C-Video (RCA), Audio (Mini Jack)		
Operating system	Windows XP / 7 / 8		
Hardware Requirement	CPU higher than P2.4GHz		
	Memory higher than 256 MB		
Frame Rate	25 fps		JE ET
USB port	USB 2.0 (Type B, UVC Webcam) USB 2.0 (Type A)	SD Card &	
Power consumption	10W	USB Thumb Drive	
Accessories	AC Power Cord, VGA Cable, Audio/Video Cable, USB Cable, HDMI Cable, Audio Convert Cable, AC Adapter, Software CD, Remote	Slots	
Shooting area	364 x 257 mm (14 x 10")	HDMI, VGA,	
		C-Vic	deo, Audio



QOMO HiteVision 866-990-QOMO info@qomo.com www.qomo.com 🍸/qomosolutions 🕒/qomohitevision 💟/qomohitevision

Copyright©2014 Qomo HiteVision, LLC. All rights reserved. This document may not be copied in any form without the permission from Qomo HiteVision, LLC. Information in this document is subject to change without notice.