

QUICK376DI ESD

LEAD FREE SELF-FEEDER&SOLDER WIRE BREAKING STATION

Features:

1. High frequency current heating, rapid heating and thermal recovery.
2. Micro computer control, digital temperature calibration, auto sleeping function.
3. Auto and manual ways of solder feeding optional, auto solder feeding mode can solder nine successive soldering joints at most.
4. Imported motor, automatic feeding, coding switch design. More functions available and adjustable, such as feeding speed, feeding length, interval time and backing time etc.
5. Two types of feeding assembly optional, easy to use.
6. Pedal switch and hand switch available.
7. Solder wire punching function.

Specifications:

Power consumption	90W
Voltage	AC 220V
Temperature range	50℃-600℃
Temperature stability	±2℃ (stationary air, no load)
Tip leak voltage	<2mV
Tip to ground resistance	<2Ω
Motor	Step motor
Feeding speed	About 2.7mm/s-27mm/s(36° /s-360° /s)
Feeding length	0-150mm
Feeding interval time	0-2.7s
Backing time	0-0.9s(about 0-25mm, regular speed: 360° /s)
Feeding mode	Auto(1-9)/Manual(0)
Diameter of solder wire	0.5, 0.6, 0.8, 1.0, 1.2mm
Weight	About 3.3kg