



More information on the website
radwag.com/en/info,w1,H5U

PUE C315 Indicator



Functions



Plus/Minus Control



Percent Weighing



Totalizing



Parts counting



Internal battery



Peak hold



Newton unit measurement



GLP Procedures



Animal weighing



ALIBI Memory

Datasheet

Metrological parameters	
Maximum quantity of verification units	6000 e
OIML Class	III
Maximum quantity of divisions from converter	838 860 ×10
Maximum increase of signal	39 mV
Minimum volatge per verification unit	0,4 μV
Maximum voltage per verification unit	3,25 μV
Minimum load cell impedance	50 Ω

Metrological parameters	
Maximum load cell impedance	1200 Ω
Load cell excitation voltage	5V DC
Connection of load cells	4 or 6 wires + shield
Physical parameters	
Display	LCD (backlit)
Device dimensions	181×136×60 mm
Packaging dimensions	220×190×90 mm
Net weight	0,6 kg
Gross weight	1,2 kg
Protection class	IP 43
Power supply	detachable adapter, akumulatory NiMH 6×AA
Number of buttons	5
Multiple range	1 or 2 ranges
Additional LCD display	WD-4/8 (option)
Communication interface	
RS232 Interface	1
Optional interfaces	RS232
Electrical parameters	
Power supply	100-240 V AC 50/60 Hz
Optional power supply	12V DC and battery
Operation time on batteries	max 7h
Environmental conditions	
Operating temperature	-10 ÷ +40 °C
Storage temperature	-10 ÷ +50 °C
Relative humidity	10% ÷ 80% RH no condensation
Construction	
Keypad	microswitch
Housing	ABS plastic



Compatible with

Waterproof stainless steel platforms
Mild steel powder coated weighing platforms
Mild steel powder coated weighing platforms
Stands, wall mounting kits and mounting brackets
Cigarette lighter receptacle power supply cables
Displays
Receipt Printer

RS 232 – Ethernet Converter
AP2-1 Current Loop Unit
RS 232, RS 485 cables
RS 232 – USB Converter
RS 232 cables (scale - EPSON printer)
RS 232 – RS 485 Converter

Software

RAD-KEY

RW Tool

Device dimensions

