



SERIES RHP REGULATORS

**SINGLE
STAGE**

RHP SERIES SPECIAL PURPOSE

- Piston actuated seat for durability
- Easy-to-read single scale 2" gauges
- Steel case construction with polycarbonate lens
- Protective rubber gauge boots
- Porous metal inlet filter
- Fine mesh filter screen between inlet and seat
- T-handle for ease of pressure adjustment
- For all your testing and evaluating needs



RHP400

Stainless steel
pressure
adjusting screw

**MAXIMUM INLET
3000 PSIG**

- RHP200** Also can be used for operating pneumatic tools such as nail guns and impact wrenches
- RHP400 and RHP800** Purging and pressure testing regulators. Designed for the HVAC-R technician
- RHP800 and RHP1500** For high pressure testing applications
- RHP3000 and RHP3680** For high pressure testing of cylinders & vessels

| PART# UPC# | RHP200* 13500 | RHP218* 13501 | RHP400 13000 | RHP418 13001 |
|-----------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| CGA INLET | NITROGEN 580 | AIR 346 | NITROGEN 580 | AIR 346 |
| OUTLET CONNECTION | 1/4" FLARE (M) | 1/4" FLARE (M) | 1/4" FLARE (M) | 1/4" FLARE (M) |
| DEL. PSIG | 5-180 | 5-180 | 20-400 | 20-400 |
| REPLACEMENT 2" GAUGES | G4S; 200 PSI G7S; 4000 PSI | G4S; 200 PSI G7S; 4000 PSI | G8S; 600 PSI G7S; 4000 PSI | G8S; 600 PSI G7S; 4000 PSI |

**RHP200; RHP400; RHP800
DIMENSIONS**

| | |
|---------|------------|
| Depth: | 4 1/4" |
| Width: | 5 3/4" |
| Height: | 5 1/4" |
| Weight: | 2 1/2 lbs. |

| PART# UPC# | RHP800 13800 | RHP818 13801 |
|-----------------------|---------------------------------|---------------------------------|
| CGA INLET | NITROGEN 580 | AIR 346 |
| OUTLET CONNECTION | 1/4" FLARE (M) | 1/4" FLARE (M) |
| DEL. PSIG | 50-800 | 50-800 |
| REPLACEMENT 2" GAUGES | G34S; 1000 PSI G7S; 4000 PSI | G34S; 1000 PSI G7S; 4000 PSI |

**RHP1500; RHP3000
DIMENSIONS**

| | |
|---------|------------|
| Depth: | 5 1/2" |
| Width: | 6" |
| Height: | 5 1/4" |
| Weight: | 3 1/2 lbs. |

**Adequate flow to operate most pneumatic equipment on the market today.*

| PART# UPC# | RHP1500 13300 | RHP1518 13301 | RHP3000 13600 | RHP3018 13601 | RHP3680 13650 |
|-----------------------|--------------------------------|--------------------------------|---------------------------------|---------------------------------|---------------------------------|
| CGA INLET | NITROGEN 580 | AIR 346 | NITROGEN 580 | AIR 346 | NITROGEN 680 |
| OUTLET CONNECTION | 1/4" NPT (F) | 1/4" NPT (F) | 1/4" NPT (F) | 1/4" NPT (F) | 1/4" NPT (F) |
| DEL. PSIG | 100-1500 | 100-1500 | 200-2500 | 200-2500 | 200-3000 |
| REPLACEMENT 2" GAUGES | G3S; 3000 PSI G7S; 4000 PSI | G3S; 3000 PSI G7S; 4000 PSI | G7S; 4000 PSI G44S; 6000 PSI | G7S; 4000 PSI G44S; 6000 PSI | G7S; 4000 PSI G44S; 6000 PSI |

For special needs such as 1/4" swage lock fittings, (panel mount, etc.), contact customer service for availability.

**RHP3680
MAXIMUM INLET
5000 PSIG**

NOTE: PSI/kPa, PSI/Kg, PSI/BAR Gauges available (Please Inquire)