



More information on the website  
[radwag.com/en/info,w1,DMO](http://radwag.com/en/info,w1,DMO)

# PMV 50 PLUS Moisture Analyzer



## Functions



Drying modes



Samples drying



Moisture content analysis



Dry mass determination



Microwave drying

## Datasheet

### Metrological parameters

Maximum capacity [Max]	50 g
Readability [d]	0,1 mg
Tare range	-50 g
Adjustment	external
Maximum sample weight	50 g
Heating module	microwawe radiation emiter
Moisture content readability	0,0001%

### Physical parameters

Display	5,7" resistive colour touchscreen
---------	-----------------------------------

Physical parameters	
Packaging dimensions	670×510×570 mm
Protection class	IP 43
Weighing pan material	glass fibre filter ø 90 mm
Communication interface	
Communication interface	RS232, 2×USB-A, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Electrical parameters	
Power supply	100-240 V AC 50/60 Hz <sup>1</sup>
Heating module power	800 W
Environmental conditions	
Operating temperature	+10 ÷ +40 °C
Features of use	
Finish mode	4 modes (automatic, manual, time-defined, user-defined)
1 100-130 V AC 50/60 Hz (version A) 200-240 V AC 50/60 Hz (version B)	

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



## Accessories

Granite Antivibration Tables  
Barcode scanners  
Moisture analyzer accessories  
Receipt Printer

Balance Storage Case  
RS 232, RS 485 cables  
RS 232 – USB Converter  
RS 232 cables (scale - EPSON printer)

## Software

RAD-KEY  
E2R System

LabVIEW Driver  
RADWAG Development Studio

## Device dimensions

