

# Charging Scale

## Charging Scale

### OCTA-WIRELESS

This reliable, electronic charging scale transmits the measurement data to the wireless display, allowing for mobile operation of the scale within a radius of 33 ft. The light, solid, aluminum housing along with the slim design, make the OCTA-WIRELESS particularly suitable for large refrigerant cylinders. Through the convenient, wireless control panel, the OCTA-WIRELESS can easily be programmed or recalibrated. REF-METER-OCTA-PLUS, the automatic charging system, is an ideal addition to the OCTA-WIRELESS. The wireless electronic charging scale is delivered in a durable carrying pouch.

#### Technical Data:

Capacity:	220 lbs
Platform:	Diameter 12.6 in Height 1.75 in
Accuracy:	+/-0.5 %
Resolution:	0.1 oz, 0.005 lbs
Power Supply:	2x 4 AAA- batteries
Battery lifetime:	60 h control panel + platform
Weight:	1.2 lbs with batteries
Signal range:	33 ft

**Part No. 4686663**



**OCTA-WIRELESS**



**OCTA-WIRELESS-KIT**

### OCTA-WIRELESS-CONTROL-BOX

Control Box for OCTA-WIRELESS

**Part No. 4686752**



**REF-METER-OCTA-PLUS**

### REF-METER-OCTA-PLUS

Automatic charging module for the OCTA-WIRELESS and REF-METER-OCTA. It is suitable for all refrigerants. Through a visual and an acoustic signal the exact programmed filling weight is achieved.

#### Technical Data:

Charging Port:	¼" SAE
Max. Valve operating pressure:	500 psi, 34 bar
Power supply:	4 x 1,5 V AA Alkaline Batteries
Battery lifetime:	> 200 hours
Materials:	Valve Body Brass, Seal Neoprene-W
Operating temperature:	0 °C to 50 °C / 32 °F to 122 °F
Weight:	1.2 lbs with batteries
Dimensions:	8.6 x 6.6 x 1.9 inch

**Part No. 4681823**



## REF-METER-OCTA

REF-METER-OCTA is a new electronic refrigerant scale built in high quality, sturdy and modern design.

- New design
- Sturdy aluminium platform
- Unique cable auto reel
- Easy to read LCD display
- Compact and lightweight (5.5 lbs)
- Large refrigerant cylinder platform
- Extremely high accuracy
- Programmable
- Field calibratable
- Supplied in a carrying pouch



### Technical Data:

Capacity:	220 lbs
Platform:	diameter 12.6 inches
Accuracy:	±0.5%
Resolution:	0.005 lbs, 0.1 oz
Power supply:	Four AAA batteries
Battery lifetime:	30 hours

**Part No. 4679462**

## REF-METER-OCTA CONTROL-BOX

Control Box for REF-METER-OCTA

**Part No. 4686813**



## REF-METER-OCTA-KIT

Combination kit including REF-METER-OCTA and REF-METER-OCTA-PLUS

**Part No. 4681989**

