

The Dual Conductor Metal Wrist Straps are a durable premium performance metal wristband that creates a reliable electrical contact to the user's wrist. The wristband provides 360-degree protection and three size options allow for conformance to most user's wrists. Meets the resistance requirements of ANSI/ESD S20.20-2014, EIA 625.



Unless otherwise noted, tolerance $\pm 10\%$
*Tolerance not variable

Specifications and procedures subject to change without notice.

Wristband

Specifications	Typical Value	
Metal	Stainless Steel	
Contact	360 degrees around wrist	
Color	Black	
Plug Size*	3.4mm	
Cord Removal Force	< 5lbs.	
Band Circumference	Min.	Max.
Small	5" (127mm)	6" (152.4mm)
Medium	5.75" (146mm)	7" (177.8mm)
Large	6.5" (165.1mm)	7.75" (196.9mm)
XLarge	7.375" (187.3mm)	8.25" (209.6mm)



Made in the
United States of America

Coil Cord

Specifications	Typical Value
Length	5 feet (1.5m)
Resistance	1 megohm
Flex Life Average	1,000,000 cycles
Plug Size*	3.4mm
Plug Type	Straight
Color	Gray

Item	Description
2381	Metal Wrist Strap with 5' Coil Cord, Small
2382	Metal Wrist Strap with 5' Coil Cord, Medium
2383	Metal Wrist Strap with 5' Coil Cord, Large
2384	Metal Wristband, Small
2385	Metal Wristband, Medium
2386	Metal Wristband, Large
2387	Metal Wristband, X-Large

DUAL CONDUCTOR METAL WRIST STRAP

926 JR Industrial Drive, Sanford, NC 27332
WEB SITE: StaticControl.com
PHONE: EAST: (919) 718-0000 | WEST: (909) 627-9634

**DRAWING
NUMBER**
2381

DATE
August
2019

SCS