



Meets ANSI/ESD S20.20 tested per ANSI/ESD S1.1 and ESD TR53.

The 2200 Series Coil Cord is for use with Single-Wire Wrist Straps and SCS Workstation Continuous Monitors (sold separately). The Coil Cord features a segmented strain relief and a single bundle of tinsel conductors which provide long cord life and flexible movement. It has a 1 megohm current limiting resistor (at the socket end to attach to the wristband). An alligator clip is included but best to plug banana plug into a banana jack ground.



Specifications	Typical Value
Tensile strength	> 15 lbs. (6.8 kg)
Flex life bending	1,000,000 cycles
Resistance end-to-end	1 Megohm $\pm$ 20%
Plug	3.4mm straight banana plug
Socket	4mm female snap socket
Color	Black

Item	Description
2210	5 ft. Coil Cord
2220	10 ft. Coil Cord

Unless otherwise noted, tolerance $\pm$ 10%

Specifications and procedures subject to change without notice.

Made in the United States of America with Globally Sourced Materials.

2200 SERIES COIL CORD

926 JR Industrial Drive, Sanford, NC 27332
WEB SITE: StaticControl.com
PHONE (919) 718-0000

**DRAWING
NUMBER**
2200 Series

DATE
July
2017

SCS