

# Pneumatic table-top test pump // -0.95...160 bar

P160.T



P160.T Basic



P160.T Solid



## Highlights

- No contamination of the test sample with oil or water
- Pneumatic up to 160 bar
- Minimal force required to reach 160 bar
- Quick exchange of test samples due to quick couplings
- Fine adjustment valve for exact setting of the test pressure

## Technical data

|                          |                             |
|--------------------------|-----------------------------|
| Type                     | P160.T                      |
| Pressure ranges          |                             |
| Vacuum                   | -0.95 bar                   |
| Overpressure             | 160 bar                     |
| Pressure medium          | Air                         |
| Connections              |                             |
| Reference pressure gauge | G¼ with quick coupling      |
| Test sample              | G¼ with quick coupling      |
| Basic                    |                             |
| Dimensions               | Approx. 470 x 262 x 170 mm  |
| Weight                   | Approx. 6 kg                |
| Solid                    |                             |
| Dimensions (case)        | Approx. 575 x 470 x 230 mm  |
| Weight                   | Approx. 10.2 kg             |
| + Adapter kit            | Brass chrome plated         |
| + Seal kit               | PA flat gaskets and O-rings |

## Article numbers

| Order code |            |                                |                |
|------------|------------|--------------------------------|----------------|
| Type       | Version    |                                | Order number   |
| P160.T     | Lever pump | Basic                          | EPPT160EBL0000 |
|            |            | Solid (incl. case and adapter) | EPPT1600BL0000 |