

Specifications

SMART Board® 6065S Pro interactive display with iQ

Model SBID-6265S-PW

Overview

The SMART Board® 6065S Pro interactive display with iQ is the hub of your meeting room.

The 4K Ultra HD LED interactive display provides optimal image clarity and wide viewing angles. SMART's exclusive and proprietary ToolSense™ technology allows a wide range of accessories to interact with applications. Unique Simultaneous Tool Differentiation allows multiple users to write simultaneously with a pen, move objects with a finger, and erase digital ink with a palm—all without switching tools, providing uninterrupted collaboration. The display's advanced HyPr Touch™ with InGlass™ touch technology provides a natural, intuitive writing and touch experience with high accuracy and low latency.




Temperature and humidity sensors help facilities managers plan resources by gaining a better understanding of a room user's environmental preferences. The display's iQ embedded computing experience offers one-touch access to collaboration tools, including a digital whiteboard, a web browser, and wireless screen sharing.

See smarttech.com for more information.

Dimensions and weights¹

Dimensions



Weight

114 lb. (51.6 kg)

Shipping dimensions (including pallet)²

67 1/8" × 46 1/2" × 10 3/8" (170.4 cm × 118.1 cm × 26.4 cm)

Shipping weight

172 lb. (78.2 kg)



As an ENERGY STAR® certified signage display, the SMART Board 6065S Pro interactive display meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

 1 All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).

2Product ships upright

Highlights

HyPr Touch with InGlass	HyPr Touch with InGlass advanced optical technology ensures highly accurate writing and drawing
ToolSense	ToolSense proprietary tool technology supports virtually unlimited pen and tool recognition
Environmental sensors	Integrated temperature and humidity sensors provide real-time measurement of the display's environmental conditions. Data is available via an included SMART app.
Ambient light sensor	Screen automatically dims or brightens, ensuring comfortable viewing in all lighting conditions

Hardware

Interaction

	Touch technology	HyPr Touch with InGlass		
	Multitouch capabilities	Up to 20 simultaneous interaction points ³		
eraser, or palm Simultaneous Tool Multiple users can touch the display and use pens and erasers at the fully collaborative experience		Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger, eraser, or palm		
		Multiple users can touch the display and use pens and erasers at the same time for a natural, fully collaborative experience		
		Multiple users can write independently and simultaneously, using different colored ink		
	ToolSense	Support for virtually unlimited pen and tool recognition		
Silktouch™ Ultra-smooth finish that allows you to use the display for hours without finger bu		Ultra-smooth finish that allows you to use the display for hours without finger burn		
Display				
	Туре	LCD with LED back light		
	Aspect ratio	16:9		
	Optimal resolution (HDMI inputs)	4K UHD (3840 × 2160) at 60 Hz		
	Brightness (maximum)	350 cd/m ²		
	Pixel dimensions	0.372 mm × 0.372 mm		
	Viewing angle	178°		
	Response time	8 ms		
	Ambient light sensor	Yes		
	Proximity sensor	Yes		
	Infrared sensor	Yes		

smarttech.com/kb/171418 2

 $^{^3}$ Chrome OS $^{\text{\tiny{W}}}$ is limited to 10 simultaneous touches, including gestures. Automatic pen recognition, plus palm, pen, and eraser differentiation are available in supported applications.

Room	temperature	and	Yes

humidity sensors

100BASE-T Ethernet Two external ports for a 4-port Fast Ethernet switched network that connects the interactive

display to a network and an external device, such as a computer

Wi-Fi IEEE 802.11A/B/G/N/Ac with 2 × 2 MIMO (both 2.4 and 5 GHz bands)

Bluetooth® Bluetooth 4.2 dual mode (backwards compatible with Bluetooth 2.1 + EDR)

Audio Two 20 W integrated speakers

Noise level <32 dBA

Included cables and accessories

1 Country-specific power cable

1 USB cable

2 Pens (red and black)

2 Eraser

1 Remote control

2 AAA batteries for the remote control

1 WM-SBID-200 wall mount

Mounting holes For a standard VESA 600 mm × 400 mm mounting plate

Lower mounting holes 11" (28 cm) from the bottom of the interactive display

Mounting bracket depth Minimum depth of 11/2" (3.7 cm) for all components on the back of the interactive display for

airflow

Accessory holes M4 mounting points located at the top, bottom, left, and right for SMART approved accessories

iQ technology

iQ experience iQ experience embedded in the display provides better performance without the need to install

a separate appliance

Included apps and features

Customizable Home screen

Whiteboard Browser Screen Share File and app libraries

Writing and drawing over any input Freeze screen and screen shade Automatic software updates

Supported languages Chinese (simplified)

Chinese (traditional)

Danish
Dutch
English
Finnish
French
German
Italian
Korean
Norwegian
Portuguese
Russian
Spanish
Swedish
Ukrainian
Vietnamese

Software

Included software iQ Android-based embedded computing

SMART Ink® and SMART Product Drivers

Subscription to SMART TeamWorks™ Room edition (included with the SMART Pro service plan

for the service plan's term)

One SMART Meeting Pro® software room license (included with SMART Pro service plan)

Subscription to SMART Remote Management for the length of warranty

Connectors



Convenience panel

- 1 HDMI® 2.0 in with HDCP 1.4 and HDCP 2.2 support
- 2 USB 3.0 Type-A (for media)
- 1 USB 3.0 Type-B (for touch)

Connector panel

- 1 Accessory slot (for OPS devices)
- 1 USB 3.0 Type-A (for media)
- 1 USB 2.0 Type-A (for service use only)
- 3 USB 3.0 Type-B (for touch)
- 2 HDMI 2.0 in with HDCP 1.4 and HDCP 2.2 support
- 1 HDMI 2.0 out
- 1 VGA in
- 1 Stereo 3.5 mm in
- 1 Stereo 3.5 mm out
- 1 S/PDIF out
- 2 RJ45
- 1 RS-232 in
- 1 RS-232 out

Back of display

- 1 AC power in
- 1 AC power out

Installation requirements

Interactive display

See the SMART Board 6000S and 6000S Pro series interactive displays installation and maintenance guide (smarttech.com/kb/171414)

IMPORTANT

The display needs an internet connection for downloading and installing important updates. Ask the network administrator to configure the network correctly for the iQ experience. For more information about network configuration, see Connecting a SMART display with the iQ experience to a network.

Room computers and guest laptops

General requirements See SMART TeamWorks software release notes or SMART Meeting Pro software release notes

4K UHD Video card that can support 3840 × 2160 resolution at 60 Hz

See Minimum requirements for Ultra High Definition or 4K on your interactive flat panel

Mini-computers

General requirements See SMART TeamWorks software release notes or SMART Meeting Pro software release notes

Dimensions Smaller than $43/4" \times 43/4" \times 11/4"$ (12 cm \times 12 cm \times 3.3 cm)

Weight Less than 10 lb. (4.5 kg)

Mounting VESA 75 mm \times 75 mm or 100 mm \times 100 mm mounting pattern (two mounting points: left and

right)

Cable requirements

HDMI Maximum length: 23' (7 m)

NOTES

- Use only certified HDMI cables that have been tested to support the performance standard you require.
- The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality.

USB 2.0 USB 2.0 certified

Hi-Speed (480 Mbps) support Maximum length: 16' (5 m)

USB 3.0 USB 3.0 certified

SuperSpeed (5 Gbps) support Maximum length: 9' (3 m)

NOTES

- SMART supports only installations that use directly connected video and USB cables, AC-powered extenders, or USB extenders purchased from SMART.
- You might be able to use higher-grade cables that are longer than specified. If you have
 problems with such a cable or an extender of any type, test the connection with a shorter
 cable before contacting SMART Support.

Important

Using cables that exceed these maximum lengths can produce unexpected results, such as degraded picture quality or USB connectivity. Refer to *Installation best practices for SMART products* (smarttech.com/kb/171035) for comprehensive information about cables and extensions for SMART hardware products.

Storage and operating requirements

Power requirements 100V to 240V AC, 50 Hz to 60 Hz

Power consumption at 77°F (25°C)

Standby mode 1.9 W

Normal operating 92 W

Operating temperature 41–95°F (5–35°C)

Storage temperature -4–140°F (-20–60°C)

Humidity 5–80% relative humidity, non-condensing

Regulatory certifications (Model ID: IDS665-1)

U.S. / Canada FCC, ISED, UL, CONEG Packaging, California Prop 65, Conflict Minerals

EU / EEA / EFTACE, RoHS Directive, Battery Directive, Packaging Directive, WEEE Directive, REACH Regulation,

POP Regulation, Radio Equipment Directive, Low Voltage Directive, CB

EAEU EAC

Australia / New Zealand RCM

Purchasing information

Order number

SBID-6265S-PW SMART Board 6065S Pro interactive display with iQ - white

Optional accessories

TS-4PEN-MC ToolSense multicolor 4-pen bundle (orange, purple, green, blue) with magnetic penwell

Other See smarttech.com/accessories

smarttech.com/kb/171418 6

SMART Board 6065S Pro interactive display with iQ - Model SBID-6265S-PW

Warranty information

SMART Assure warranty Includes advanced hardware replacement and access to onsite support. Terms and conditions vary by region. Contact your local reseller or distributor for information and visit smarttech.com/warranty.

smarttech.com/support smarttech.com/contactsupport

© 2020 SMART Technologies ULC. All rights reserved. SMART Board, SMART Ink, SMART TeamWorks, SMART Meeting Pro, Pen ID, HyPr Touch, Object Awareness, Silktouch, ToolSense, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. The Bluetooth word mark is owned by the Bluetooth SIG, Inc. and any use of such marks by SMART Technologies ULC is under license. The Adopted Trademarks HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. April 14, 2020.