Specifications

SMART Board™ Interactive Whiteboard

Model SBD685

Physical Specifications

Size 77 1/2" W × 50 5/8" H × 5 1/8" D

(196.9 cm × 128.6 cm × 13 cm)

Active Screen Area 74" W × 46 1/8" H (188 cm × 117.2 cm)

(maximum interactive, 87 1/8" (221.3 cm) diagonal,

projected image) 16:10 aspect ratio

Weight 42 lb. (19.1 kg)

Shipping Size

1 unit 54" W × 86 1/4" H × 5 1/2" D

 $(137.2 \text{ cm} \times 219.1 \text{ cm} \times 14 \text{ cm})$


8 units on pallet 55" W × 90 3/4" H × 45" D

 $(139.7 \text{ cm} \times 230.5 \text{ cm} \times 114.3 \text{ cm})$

Shipping Weight

1 unit 72 lb. (32.7 kg)

8 units on pallet 591 lb. (268.1 kg)



All dimensions +/- 1/8" (0.3 cm). All weights +/- 2 lb. (0.9 kg).



Standard Features

Software Includes SMART Notebook software. See the <u>SMART Notebook software</u>

specifications for a complete list of system requirements. Software upgrades

are available from www2.smarttech.com/st/en-US/Support/SBS/.

Dual Touch/Dual Write Enables two users to work simultaneously in SMART Notebook software

Pen Tray Optical sensors in the pen tray detect when you lift one or two pens, or the eraser,

from the tray. LEDs indicate the active tools.

Pens and Eraser Black, red, green and blue pen tray pens and a rectangular eraser

Resolution Touch resolution is approximately 4000 × 4000.

Screen Surface The hard-coated surface is tear proof, optimized for projection, compatible

with dry-erase markers and cleans easily with whiteboard cleaner.

Digitizing Technology Resistive technology

Frame Finish Dark gray (approximates Pantone® Charcoal Gray 18-0601 TPX) and

Ultrasonic Chrome (approximates metallic Pantone 877C)

Wall-Mount Bracket Includes two 32" (81.3 cm) wide brackets, ten screws and ten drywall anchors

to support your wall-mounted interactive whiteboard

Computer Connection 16' (5 m) USB 2.0 cable

Power Requirements Power is obtained from your computer directly through the USB cable for Windows®,

Mac and Linux® computers. Power consumption is less than 1.5 W (300mA at 5V).

Certifications and Compliance

CSA (U.S./Canada), CE, CB (TUV), China EIP, RoHS (Europe) and WEEE

Warranty Five-year limited equipment warranty upon registration. See included warranty

document for details.

Theft Prevention Features a pen tray locking feature and a Kensington® security slot on the pen tray

NOTE

A digital projector isn't included with this model of SMART Board interactive whiteboard. To take full advantage of all interactive features, you must integrate a 16:10 aspect ratio digital projector.

Storage and Operating Specifications

• Maximum storage temperature: 122°F (50°C)

Minimum storage temperature: -40°F (-40°C)

Operation 41°F to 95°F (5°C to 35°C) with up to 80% humidity, non-condensing

SMART Order Number

SBD685 87 1/8" (221.3 cm) diagonal dual-touch SMART Board 685 interactive whiteboard

Optional Accessories

NOTE

The RS-232 to USB conversion module and WC6 wireless Bluetooth® connection option aren't available for this model.

Part Number	Description	NA	UK	EU	AU
SBA-XX*	USB audio system with two 15 W speakers mounts on your interactive whiteboard or the wall	✓	✓	✓	✓
SYSON6-XX*	SystemOn expansion module wakes up your computer and turns on your projector with one button press	✓	✓		
USB-GW	GoWire™ SMART Notebook software auto-launch cable				
USB-XT	16' (5 m) USB active extension cable				
CAT5-XT	Cat 5 to USB cable extender set				
RPEN-ER	Replacement set of four pen tray pens (black, red, green and blue) and a rectangular eraser				
RPEN	Replacement set of four pen tray pens (black, red, green and blue)				


*Part numbers ending in XX include region-specific power supplies for the countries or regions indicated by ✓ at the right. When ordering, substitute XX in the part number with the appropriate country code, as follows:

- NA = U.S. and Canada
- UK = United Kingdom
- EU = European Union
- AU = Australia

Physical Dimensions


Wall-Mounted Cut Away View

Leave at least 5/8" (1.6 cm) headroom to wall-mount your interactive whiteboard.




The distance from the bottom of the wall-mount bracket to the top of your installed interactive whiteboard is 4 1/4" (10.8 cm).

Wall-Mounted Side View



Wall-Mounted Front View



The recommended wall-mounted installation height to the top of your SMART Board SBD685 interactive whiteboard for average-sized adults is 81 3/4" (207.6 cm).

USB Connection Location

All dimensions +/- 1/8" (0.3 cm).

SMART

www.smarttech.com/support www.smarttech.com/contactsupport Support +1.403.228.5940 or Toll Free 1.866.518.6791 (U.S./Canada)