

# Speakers



## Lay-In Speaker SP-628L

SP-628L 2-Way, Lay-in Ceiling Speaker Assembly

### Specifications

Frequency Range	120 Hz to 21 kHz, $\pm$ 6 dB
Power	30 Watts Continuous
Sensitivity	87 dB SPL (1W/1M)
Impedance	8 $\Omega$
Nominal Coverage	90° x 90°
LF Driver	6.5" Cone Driver
Magnet	10 oz
HF Driver	High efficiency 1" domed tweeter
Enclosure Material	Air Sealed Metal Backcan
Termination	Screw terminals for secure speaker wire connection
Mounting	Attached "T" Bar support
Dimensions (H x W x D)	12.25" x 23.75" x 6.25" (13" with "T" Bar support)
Net Weight (ea)	8 lb
Shipping Weight (box of 4)	39 lb
UL Requirement	Meets UL 2043 criteria for plenum installation

### Features

- Complete speaker assembly (12" X 24")
- Perforated steel grill
- Heavy duty support for anti rattle or movement
- Attached adjoining T-bar
- Air Sealed Metal Back Can for an infinite baffle
- Screw terminal
- 3 pre-installed brackets for safety wire
- Completely painted, tile white
- No speaker assembly required
- Quick and efficient installation