

Specifications

SMART kapp iQ

SMART kapp iQ® 75 board

Overview

With a SMART kapp iQ® 75 board, you can capture notes and ideas, present information and collaborate with others in simple but powerful ways.

Connect a Bluetooth®-enabled mobile device to the board by scanning the Quick Response (QR) code on the board's screen. When you first connect your mobile device, you're directed to the Apple App Store or Google Play™ to download the SMART kapp® app. After installing the app, you can connect to your board and share notes with others. You can write notes in black or red ink using the provided pens and erase notes with the pens' erasers or with your palm or fist.


The board's 4K ultra-high-definition resolution display provides optimal image clarity and viewing from any angle.

See education.smarttech.com for more information about SMART kapp iQ.



Dimensions and weights¹

Dimensions



Weight

185 lb. (84 kg)

Shipping dimensions (including pallet)

75 3/8" × 54 3/8" × 14"
(191.6 cm × 138 cm × 35.5 cm)

Shipping weight

238 lb. (108 kg)



As an ENERGY STAR® certified signage display, the SMART Board® 6075 interactive flat panel meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

¹All dimensions ± 1/8" (0.3 cm). All weights ± 2 lb. (0.9 kg).

Hardware

Interaction

Touch technology	DViT® (Digital Vision Touch) technology
Multitouch capabilities	8 touches ²
Object awareness	Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger, eraser or palm.
Pen ID™	Two people can write independently and simultaneously, using different colored ink.

Display

Type	LED
Aspect ratio	16:9
Optimal resolution	3840 × 2160 at 30 Hz (HDMI®) or 60 Hz (DisplayPort)
Horizontal frequency	122–140 kHz (typically 135 kHz)
Vertical frequency	47–63 Hz (typically 60 Hz)
Contrast ratio (typical)	5000:1
Brightness (maximum)	360 cd/m ²
Pixel dimensions	0.429 mm × 0.429 mm
Gamut	72% of NTSC
Viewing angle	178°
Response time (typical)	8 ms

Presence detection Presence detection sensor on the bottom frame

Audio 10 W integrated speakers (×2)

Noise level <35 dBA

Included cables and accessories SMART kapp iQ appliance
8' (2.4 m) country-specific power cable
Pen (×2)

SMART kapp iQ appliance

Wireless technology	Bluetooth 4.0 dual mode (backwards compatible with Bluetooth 2.1 + EDR)
Capture options	Establish a Bluetooth wireless connection with a supported mobile device (see below) by scanning the interactive display's unique QR code

²Requires SMART Product Drivers to be installed. Some applications might not support 8 touches.

Supported languages French
 German
 Italian
 Japanese
 Korean
 Norwegian
 Simplified Chinese
 Spanish
 Swedish
 Traditional Chinese

Mounting holes For a standard VESA® 600 mm × 400 mm mounting plate
 Lower mounting holes 13 3/4" (35 cm) from the bottom of the interactive flat panel

Mounting bracket depth Minimum depth of 1 5/8" (4.2 cm) for all components on the back of the interactive display to clear the wall

Connectors

Side

Connector panel

OPS slot (for the iQ appliance)
 HDMI1 input connectors
 HDMI in
 USB Type-B
 HDMI2 input connectors
 HDMI in
 USB Type-B
 DisplayPort input connectors
 DisplayPort in
 USB-Type-B
 Stereo 3.5 mm out
 RS-232 in

SMART kapp iQ appliance

USB 3.0 Type-A (×2)
 USB 2.0 Type-B³
 OPS/HDMI input connectors
 HDMI in
 USB Type-B
 HDCP encrypted HDMI 1.4 out
 RJ45

Bottom

USB 2.0 Type-A

Back

AC power inlet

Installation requirements

Board

See the *SMART kapp iQ boards administrator's guide* (smarttech.com/kb/171038)

³For service use only

SMART kapp® app

Apple devices iOS 9 or later operating system software
50 MB of storage
iPhone 4S or later
Third-generation iPad or later
First-generation iPad mini or later
Fifth-generation iPod touch or later

Android™ devices Android 4.4.4 (KitKat) or later operating system
50 MB of storage (internal or SD card)
1024 MB of RAM
720p or better screen resolution
Bluetooth 2.1 + EDR
3 megapixel or better rear-facing camera (recommended)

SMART kapp viewer

Mobile Safari for iOS 9 or later operating system software
Chrome™ for Android 39.0.2171.93 or later

Desktop Internet Explorer® 10 or later
Chrome 39.0.2171.95 or later
Firefox® 34.0.5 or later
Safari 8.0 or later

Room computers and guest laptops

General requirements See the [SMART Notebook software release notes](#)

4K UHD Graphics card that can support 3840 × 2160 resolution at 30 Hz and that has 1 GB DDR 5 memory
See [Minimum requirements for Ultra High Definition or 4K on your interactive flat panel](#)

Mini-computers

General requirements See the [SMART Notebook software release notes](#)

Dimensions Smaller than 10" × 10" × 2" (25.4 cm × 25.4 cm × 5.1 cm)

Weight Less than 10 lb. (4.5 kg)

Mounting VESA 75 mm × 75 mm or 100 mm × 100 mm mounting pattern

Cable requirements

HDMI Maximum length: 23' (7 m)

 **NOTES**

- Use only certified HDMI cables that have been tested to support the performance standard you require.
 - The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality.
-

DisplayPort DisplayPort 1.2 compliant or better
Maximum length: 23' (7 m)

USB	Maximum length: 16' (5 m)
Important	Using cables that exceed these maximum lengths can produce unexpected results, such as degraded picture quality or USB connectivity. Refer to <i>SMART installation standards</i> (smarttech.com/kb/171035) for comprehensive information about cables and extensions for SMART hardware products.

Storage and operating requirements

Power requirements	100V to 240V AC, 50 Hz to 60 Hz
Solution power consumption at 77°F (25°C)	
Standby mode	19 W
Normal operating	190 W
Maximum operating	315 W
Standalone interactive flat panel power consumption at 77°F (25°C)	
Standby mode	<2 W
Normal operating (out-of-box)	<131 W
Operating temperature	41–95°F (5–35°C)
Storage temperature	-4–140°F (-20–60°C)
Humidity	5–80% relative humidity, non-condensing

Certification and compliance

Regulatory certification	UL (U.S./Canada), FCC, IC, EMC, LV, VCCI, PSE, KC Mark
Environmental compliance	
European Union	REACH, RoHS, WEEE and Packaging
U.S.	Packaging and Conflict Minerals

Purchasing information

Order number	
KAPP-IQ75	SMART kapp iq 75 board
Optional accessories	
WM-SBID-501	Fixed wall mount for SMART Board interactive displays
Other	See smarttech.com/accessories
Warranty	Two-year limited equipment warranty

smarttech.com/support
smarttech.com/contactsupport

© 2016–2017 SMART Technologies ULC. All rights reserved. SMART kapp, SMART kapp IQ, SMART Board, DViT, Pen ID, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. iPhone, iPad, iPod touch and Safari are trademarks of Apple Inc., registered in the U.S. and other countries. Google Play, Android and Chrome are trademarks of Google Inc. The Bluetooth word mark is owned by the Bluetooth SIG, Inc. and any use of such marks by SMART Technologies ULC is under license. "HDMI" and all associated logos are trademarks of HDMI Licensing, LLC. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. 10/2017.