

# MULETAPE®, ROPE, GRIPS™, AND LINES



1-855-798-6657 | SOUTHWIRETOOLS.COM

©2017 Southwire Company, LLC. All rights reserved. ®Registered Trademark and ™Trademark of Southwire Company, LLC. MULETAPE® is a registered trademark of NEPTCO Inc.

BUILT FOR DURABILITY. BUILT FOR RELIABILITY. BUILT FOR WORK."



Southwire<sup>™</sup> | TOOLS & EQUIPMENT

## Southwire MULETAPE<sup>®\*</sup>

Southwire MULETAPE pulling line increases pulling and installation efficiency on jobsites. It allows you to thread, measure and pull with a single product.

- Durable, low friction polyester tape
- Printed with accurate sequential footage markings
- Replaces pull line, conduit measuring tape and rope in most applications



#### SWMT2500-3000S

SWMT1800-3000S



SWMT1250-3000S



SWMT400-4500P

10 LB SOUTHWIRE

\*Actual size

MULETAPE® is a registered trademark of NEPTCO Inc.

# **Southwire Conduit Measuring Tape**

The 3,000 ft conduit measuring tape has easy-to-read markings in sequential one-foot increments.

- Provides quick and accurate measurement of conduit runs
- Printed with accurate sequential footage markings
- Will not rot or mildew

160 LB SOUTHWIRE

#### SWCMT160-3000S

\*Actual size

### **Southwire Poly Line**

Poly line for light duty cable or rope pulling applications.

- Ready-to-use storage container quickly dispenses a tangle-free line
- Line is resistant to rot and mildew
- Use to pull electrical and communication wire





# **QWIKrope**<sup>®</sup>

An innovative, new, high performance pulling rope that is UV resistant, lightweight and ultra low stretch

- High performance pulling rope made from ultra high molecular weight polyethylene fibers
- 12 Strand, single braided 9/16" pulling rope with a breaking strength of 32,000 lbs.



# **Southwire Double Braided Pulling Rope**

Cable pulling rope designed for high breaking strength with low stretch. The double braid weave provides enhanced strength and increased pulling capability.

- High strength and low stretch
- Resistant to UV rays, chemicals and abrasions
- Factory spliced pulling eye at each end
- Polyester double braid

### **GRIPS<sup>™</sup> Pulling Heads**

Dual lock pulling system using both a cam lock head and a double braided wire to quickly secure cable to rope without the fear of losing a conductor

- Double lock system
- Each double lock Maxis<sup>®</sup> Grips<sup>™</sup> head rated at 4000 lbs.
- Holds securely to NO-LUBE® wire
- Disconnect wire from pulling heads in 2 minutes without cutting the wire



### **Pulling Head and Grips**

Wire pulling accessories include light duty pulling grips and pulling heads.



#### Muletape® Pull Line

| A NUMBER OF STREET | MODEL #        | STOCK # | DESCRIPTION   | WIDTH | LENGTH    | AVG.<br>BREAKING<br>STRENGTH | Package          |
|--------------------|----------------|---------|---|-------|-----------|------------------------------|------------------|
| l                  | SWMT400-4500P  | 645850  | MULETAPE <sup>®</sup> Pull Line 400lb 4500ft Pail   | 1/4"  | 4,500 Ft. | 400 lbs.                     | Bucket           |
|                    | SWMT1250-3000S | 645851  | MULETAPE® Pull Line 1250lb 3000ft Spool             | 1/2"  | 3,000 Ft. | 1,250 lbs.                   | Plastic<br>Spool |
|                    | SWMT1800-3000S | 645852  | MULETAPE <sup>®</sup> Pull Line 1800lb 3000ft Spool | 5/8"  | 3,000 Ft. | 1,800 lbs.                   | Plastic<br>Spool |
|                    | SWMT2500-3000S | 645854  | MULETAPE®Pull Line 2500lb 3000ft Spool              | 3/4"  | 3,000 Ft. | 2,500 lbs.                   | Plastic<br>Spool |





#### **Conduit Measuring Tape**

| MODEL #        | STOCK # | DESCRIPTION                               | WIDTH | LENGTH   | AVG.<br>BREAKING<br>STRENGTH | Ŭ               |
|----------------|---------|---|-------|----------|------------------------------|-----------------|
| SWCMT160-3000S | 645849  | Conduit Measuring Tape 160lb 3000ft Spool | 3/16" | 3000 Ft. | 160 lbs                      | Metal<br>Flange |



|   |         |         |                    |                  |                  |                   |       |       |        |          | -                 |
|---|---------|---------|--------------------|------------------|------------------|-------------------|-------|-------|--------|----------|-------------------|
|   | 1000    |         | in the man will be |                  |                  | PULLING<br>JACKET |       | ROPES | SWIVEL | CARRYING | DOUBLE<br>LOCKING |
|   | MODEL # | STOCK # | MAXIS GRIPS        | # OF<br>GRIPS    | WIRE<br>SIZES    | MED               | LARGE | LARGE | SMALL  | BAG      | HEAD              |
|   | GP110   | 568227  | COMPLETE SET       | COMPLET<br>E SET | 1/0 - 750<br>MCM | x                 | x     | x     | x      | x        |                   |
| Γ | GP00AA  | 568228  | GROUP AA           | 4 GRIPS          | 1/0 - 4/0        |                   |       |       |        |          |                   |
| Γ | GP101A  | 568229  | GROUP A            | 4 GRIPS          | 3/0 - 4/0        |                   |       |       | х      | х        | Х                 |
|   | GP102B  | 568230  | GROUP B            | 4 GRIPS          | 250 -<br>350MCM  | x                 |       |       | x      | x        | х                 |
|   | GP103C  | 568231  | GROUP C            | 4 GRIPS          | 400 -<br>500MCM  |                   | x     | x     |        | x        | х                 |
|   | GP104D  | 568232  | GROUP D            | 4 GRIPS          | 600 -<br>750MCM  |                   | х     | x     |        | x        | x                 |



#### Pulling Heads and Grips

| MODEL # | STOCK #  | DESCRIPTION                               | WIRE SIZES                             | Pulling Force Capacity |
|---------|----------|---|--|------------------------|
| WPG3/4  | 582808   | 3/4" Pulling Grip                         | 3/4"                                   | 100 lbs.               |
| WPG1/2  | 582810   | 1/2" Pulling Grip                         | 1/2"                                   | 100 lbs.               |
| CSPH1HD | 58294505 | SIMpull Gripit™ Circuit Size Pulling Head | Up to 7 wires of 10-14<br>AWG Solid or | 700lbs at clip         |



# Poly Line

| 1.00.00 | MODEL # | STOCK # | DESCRIPTION                                | WIDTH | LENGTH    | AVG.<br>BREAKING<br>STRENGTH | Package  |
|---------|---------|---------|--|-------|-----------|------------------------------|----------|
| ŝ       | PL6500  | 582805  | 6,500' 210 lbs. Tensile Strength Poly Line | 3/16" | 6,500 Ft. | 210 lbs                      | Bucket   |
| ~       | PL500   | 582806  | 500' 210 lbs. Tensile Strength Poly Line   | 3/16" | 500 Ft.   | 210 lbs                      | Canister |

# QwikRope®

| MODEL # | STOCK # | DESCRIPTION  | DIAMETER | LENGTH    | AVG.<br>BREAKING<br>STRENGTH | TOTAL<br>WEIGHT |
|---------|---------|--|----------|-----------|------------------------------|-----------------|
| SPR183  | 583874  | QWIKrope® 1/8" X 300', 12 Strand UHMWPE Rope<br>AVG. Break. 1,100 lb.                | 1/8"     | 300 FT.   | 1,100 LB.                    | 2.5 LB.         |
| SPR143  | 583875  | QWIKrope® 1/4" X 300', 12 Strand UHMWPE Rope<br>AVG. Break 7,500 lb.                 | 1/4"     | 300 ft.   | 7,500 lb.                    | 6.5 lb.         |
| SPR146  | 585263  | QWIKrope® 1/4" X 600', 12 Strand UHMWPE Rope<br>AVG. Break 7,500 lb.                 | 1/4"     | 600 ft.   | 7,500 lb.                    | 11 lb.          |
| SPR963  | 583056  | QWIKrope <sup>®</sup> 9/16" X 300', 12 Strand UHMWPE<br>Rope AVG. Break. 32,000 lb.  | 9/16"    | 300 ft.   | 32,000 lb.                   | 26 lb.          |
| SPR966  | 583057  | QWIKrope <sup>®</sup> 9/16" X 600', 12 Strand UHMWPE<br>Rope AVG. Break. 32,000 lb.  | 9/16"    | 600 ft.   | 32,000 lb.                   | 52 lb.          |
| SPR969  | 583058  | QWIKrope <sup>®</sup> 9/16" X 900', 12 Strand UHMWPE<br>Rope AVG. Break. 32,000 lb.  | 9/16"    | 900 ft.   | 32,000 lb.                   | 77 lb.          |
| SPR9612 | 583059  | QWIKrope <sup>®</sup> 9/16" X 1200', 12 Strand UHMWPE<br>Rope AVG. Break. 32,000 lb. | 9/16"    | 1,200 ft. | 32,000 lb.                   | 103 lb.         |

# Pulling Rope

| MODEL # | STOCK # | DESCRIPTION  | DIAMETER | LENGTH   | AVG.<br>BREAKING<br>STRENGTH | TOTAL<br>WEIGH |
|---------|---------|--|----------|----------|------------------------------|----------------|
| P-963   | 568235  | 9/16 inch 300 ft., Double Braided Composite Rope<br>AVG. Break. 16,000 lb. | 9/16"    | 300 ft.  | 16,000 lb.                   | 50 LB.         |
| P-966   | 568236  | 9/16 inch 600 ft., Double Braided Composite Rope<br>AVG. Break. 16,000 lb. | 9/16"    | 600 FT.  | 16,000 lb.                   | 75 LB.         |
| P-583   | 568237  | 5/8 inch 300 ft., Double Braided Composite Rope<br>AVG. Break. 18,000 lb.  | 5/8"     | 300 FT.  | 18,000 lb.                   | 63 LB.         |
| P-586   | 568239  | 5/8 inch 600 ft., Double Braided Composite Rope<br>AVG. Break. 18,000 lb.  | 5/8"     | 600 FT.  | 18,000 lb.                   | 85 LB.         |
| P-786   | 568240  | 7/8 inch 600 ft., Double Braided Composite Rope<br>AVG. Break. 32,000 lb.  | 7/8"     | 600 FT.  | 32,000 lb.                   | 240 LB.        |
| P-789   | 577913  | 7/8 inch 900 ft., Double Braided Composite Rope<br>AVG. Break. 32,000 lb.  | 7/8"     | 900 FT.  | 32,000 lb.                   | 269 LB         |
| P-7812  | 568241  | 7/8 inch 1200ft, Double Braided Composite Rope                             | 7/8"     | 1200 FT. | 32,000 lb.                   | 298 LB         |









# MULETAPE®, ROPE, GRIPS™, AND LINES





@SOUTHWIRETOOLS

@SOUTHWIRETOOLS

SOUTHWIRETOOLS

1-855-798-6657 | SOUTHWIRETOOLS.COM

©2017 Southwire Company, LLC. All rights reserved. ®Registered Trademark and ™Trademark of Southwire Company, LLC. MULETAPE® is a registered trademark of NEPTCO Inc.

/SOUTHWIRETOOLS

/SOUTHWIRETOOLSLATINO

BUILT FOR DURABILITY. BUILT FOR RELIABILITY. BUILT FOR WORK."