GAGE BLOCKS

INDIVIDUAL RECTANGULAR GAGE BLOCKS

HOW TO ORDER

RECTANGULAR BLOCK SIZES

- Width: all blocks are .352" wide
- Length: for blocks under .050", length is 1.115"
- For blocks with .050" through .190", length is 1.180"
- For blocks .200" and above, length is 1.380"

EXCEPTIONS

- 28 block sets with blocks to .090" are all 1.115" long
- .050, .060, .070, .080, .090" blocks in this set are listed with the suffix "ss".
- .050, .100, .150" blocks contained in the 81–92-piece sets are 1.380" long. Specify "long length".
- .100" blocks contained in the 36, 38, and 43-block sets are 1.380" long. Specify "long length".

Specify in this Sequence: Shape, Material, Size and Accuracy Grade						
Shape	Materia	Size	Accuracy			
R=Rectangular	S=Steel					
S=Square	C=croblox	Listed in table	Listed in table			
	Y=Ceramic					

Example: RS .250A1 = Rectangular Steel block, size .250, Grade A1 Accuracy

INCH	
------	--

croblox®, Ceramic and Steel Gage Blocks	croblox®		Ceramic		Steel
Grosion ; corarino ana otoci dago bicono	A1	AA	A1	AA	A1
Grade	0	00	0	00	0
0.010	•	•			•
0.0101					•
.0101 Through .0109 in Steps of .0001					•
.011 Through .019 in Steps of .001					•
.020 (Wear Blocks)	•				
.020 or .02005	•	•			•
.0201 Through .0209 in Steps of .0001	•	•			•
.021 Through .029 in Steps of .001	•	•			•
0.03	•	•			•
0.04	•	•			•
.050 long*	•	•	•	•	•
.050 (Wear Blocks)	•				
.050S or .050SS	•	•			•
0.0501					•
.0501 Through .0509 in Steps of .0001					•
.051 Through .059 in Steps of .001					•
.060 or .060SS	•	•			•
.0625 (1/16)	•	•	•	•	•
.070 or .070SS	•	•			•
.078125 (5/64)		•			
.080 or .080SS	•	•			•
.090 or .090SS	•	•			•
.09375 (3/32)	•	•	•	•	•
.100 long*	•	•	•	•	•
.100 (Wear Blocks)	•				
.100S	•	•			
0.1000	•	•	•	•	•
0.1001	•	•	•	•	•
0.1001	•	•	•	•	•
.1001 Through .1009 in Steps of .0001		•			
.101 Through .109 in Steps of .001	•	•	•	•	•
.109375 (7/64)	•	•	•		•
.110 Through .119 in Steps of .001	•	•	•	•	•
.120 Through .129 in Steps of .001	•	•			
.130 Through .139 in Steps of .001	•	•	•	•	•
.140 Through .149 in Steps of .001	•	•			•
.150 Long*	•	•	•	•	•
0.15		•			
.160 Through .190 in Steps of .010	•	•	•	•	•
.200, .250, .300, .350	•	•	•	•	•
.400, .450, .500, .550, .600	•	•	•	•	•
.650, .700, .750	•	•		•	
.800, .850, .900, .950	•	•			•
1.000	•	•		•	•
2,000					
3.000		•			•
4.000	•	•	•	•	•
5.000					•
6.000					•

^{*} Order long length for Webber set replacements.



