



UPS-33020-02

TECHNICAL DESCRIPTION

The UPS-33020-02 shall be a tower on-line UPS unit in a steel and plastic enclosure. It shall operate at 208 3-phase wye volts AC at both 50 or 60Hz and has a hard-wired input and output. This unit can accommodate additional battery cabinets to extend it autonomous run time. Overall dimensions shall be 40.0"H x 12.0"W x 34"D. Weight shall be 508 pounds. The UPS-33020-02 shall have a total load rating of 20,000VA / 20,000 Watts. This unit can accommodate an optional SNMP network card for unit monitoring and shutdown.

SPECIFICATIONS	UPS-33020-02
Load Rating	67A In
Voltage Rating	3φY, 208/120V (5 wire)
Power Requirement (no load)	1.4 kW Max
Input/Mains Plug Type	Terminal Strip
Input/Mains Cord Length	None
# of Receptacles	1
Receptacle Type	Terminal Strip
Over-Current Auto Shutdown	Circuit Breaker
Over-Temperature Auto Shutdown	Internal temperature fault shutdown
Network Port	Requires SNMP card
Serial Port	RS-232 on Female 9-pin D-subminiature USB Type B RJ45 on optional SNMP card
Temperature Sensor Input	None
BTU/h Max	5140 BTU/h
Auxiliary Relay Outputs	No
Contact Closure Input	EPO
Dimensions	12" W x 34" D x 40" H
Weight	508 lbs
Temperature Range:	0C to 40C
Humidity Range	< 95% R.H. Non-condensing
Agency Listings	UL 1778 CSA C22.2 No.107.3-14

** Specifications subject to change without notice
Specifications Version: ESP-SRX_Product_Specs_Master 03.20.20.xlsx

