



XT Soldering tips

- XT Series Tips for WXP 120/ WP 120 Soldering Pencils
- Most difficult, high mass soldering jobs
- Maximum power and response for top performance
- Optimal balance between power, control and running costs with wide range of tips
- Highest quality soldering standard for widest range of applications.






Power Response XT





Chisel shape



A = Width mm
B = Thickness mm
C = Length mm

| Model | A | B | C | PU | Order No. |
|---|-----|------|------|----|----------------|
| XT A | 1.6 | 0.7 | 37 | 1 | T005 44 703 99 |
|  | | | | | |
| XT AL | 1.6 | 1.0 | 40 | 1 | T005 44 701 99 |
|  | | | | | |
| XT B | 2.4 | 0.8 | 36 | 1 | T005 44 704 99 |
|  | | | | | |
| XT BSC | 2.5 | 0.8 | 36.3 | 1 | T005 44 738 99 |
|  | | | | | |
| XT BSL | 2.4 | 0.45 | 36 | 1 | T005 44 741 99 |
|  | | | | | |

| Model | A | B | C | PU | Order No. |
|---|-----|------|----|----|----------------|
| XT BX 30° | 2.4 | 0.8 | | 1 | T005 44 744 99 |
|  | | | | | |
| XT C | 3.2 | 0.8 | 36 | 1 | T005 44 705 99 |
|  | | | | | |
| XT CSL | 3.2 | 0.45 | 36 | 1 | T005 44 742 99 |
| XT D | 4.6 | 0.8 | 35 | 1 | T005 44 706 99 |
| XT DL | 4.6 | 0.8 | 40 | 1 | T005 44 736 99 |
| XT D 45° | | | 37 | 1 | T005 44 721 99 |
| XT E | 5.9 | 1.2 | 35 | 1 | T005 44 707 99 |
| XT H | 0.8 | 0.4 | 37 | 1 | T005 44 713 99 |
| XT HX | 0.8 | 0.4 | | 1 | T005 44 737 99 |
| XT M | 3.2 | 1.2 | 40 | 1 | T005 44 702 99 |
| XT MX | 3.2 | 0.8 | | 1 | T005 44 745 99 |



Round



A = Width mm
B = Thickness mm
C = Length mm

| Model | A | B | C | PU | Order No. |
|--------------|-----|---|----|----|----------------|
| XT BS | 2.4 | | 37 | 1 | T005 44 715 99 |



| Model | A | B | C | PU | Order No. |
|--------------|-----|---|----|----|----------------|
| XT CS | 3.2 | | 37 | 1 | T005 44 716 99 |
| XT DS | 5.0 | | 35 | 1 | T005 44 717 99 |



Bevel Cut



A = Width mm
B = Thickness mm
C = Length mm

| Model | A | B | C | PU | Order No. |
|------------------|-----|---|----|----|----------------|
| XT AA 60° | 1.6 | | 37 | 1 | T005 44 708 99 |
| XT BB 45° | 2.4 | | 37 | 1 | T005 44 709 99 |
| XT CC 45° | 3.2 | | 37 | 1 | T005 44 710 99 |



| Model | A | B | C | PU | Order No. |
|-----------------|-----|---|------|----|----------------|
| XT DDH45 | 4 | | 40.5 | 1 | T005 44 730 99 |
| XT F 30° | 1.2 | | 37 | 1 | T005 44 718 99 |



Conical




A = Width mm
B = Thickness mm
C = Length mm

| Model | A | B | C | PU | Order No. |
|-------------|-----|---|----|----|----------------|
| XT O | 1.0 | | 37 | 1 | T005 44 714 99 |





Gullwing



A = Width mm
B = Thickness mm
C = Length mm

| Model | A | B | C | PU | Order No. |
|---------------|---|---|----|----|----------------|
| XT GW1 | | | 37 | 1 | T005 44 712 99 |



Knife



A = Width mm
B = Thickness mm
C = Length mm

| Model | A | B | C | PU | Order No. |
|--------------|-----|---|----|----|----------------|
| XT KN | 2.0 | | 45 | 1 | T005 44 711 99 |



External thread

A = Width mm
B = Thickness mm
C = Length mm

| Model | A | B | C | PU | Order No. |
|------------------------------------|----|---|----|----|----------------|
| XT External thread, refined | M4 | | 36 | 1 | T005 44 719 99 |



XTR Soldering tips

Chisel shape



A = Width mm
B = Thickness mm
C = Length mm

| Model | A | B | C | PU | Order No. |
|--------------|-----|-----|------|----|----------------|
| XTR A | 1.6 | 0.7 | 36.5 | 1 | T005 44 723 99 |
| XTR B | 2.4 | 0.8 | 36 | 1 | T005 44 724 99 |



| Model | A | B | C | PU | Order No. |
|--------------|-----|-----|------|----|----------------|
| XTR E | 5.9 | 1.2 | 34.5 | 1 | T005 44 727 99 |
| XTR M | 3.2 | 1.2 | 39.5 | 1 | T005 44 728 99 |

