



# AIRPRO® MICROMANOMETER INSTRUMENTS

MOBILE APP, FEATURE SETS, AND MICROMANOMETER

AirPro® Micromanometer Instruments are rugged, compact, configurable and highly accurate measurement devices featuring a Micromanometer (AP800), Mobile Application Software, and Feature Sets (Basic, Advanced and Professional).

AirPro Micromanometer Model AP800 measures static and differential pressures with seamless connection to smart devices, utilizing Bluetooth® Low Energy (BLE). Data is shown on an integrated display on the instrument while simultaneously being communicated wirelessly, in real-time, to the AirPro Mobile Application Software running on your mobile Android or iOS handheld device. Instrument features are enabled remotely based on user preference and subscription level.

#### **Applications**

- + HVAC commissioning and troubleshooting
- + Testing and balancing
- + Pitot tube duct traverses
- + Static pressure measurements
- + Differential pressure measurements

#### **Features and Benefits**

- + Calculates velocity when used with a pitot tube
- + Auto zeros pressure sensor upon instrument startup
- + Barbed pressure ports to securely attach tubing
- + High contrast display eases viewing in dimly lit areas
- + Measure differential and static pressures from -15 to +15 in.  $H_2O$  (-3735 to +3735 Pa)
- + Long life rechargeable Li-ion battery reduces cost of ownership
- + Calibration certificate included



## AIRPRO MOBILE APPLICATION SOFTWARE

The AirPro Mobile software supports both Android or iOS smart devices and is available in three levels of performance - Basic, Advanced and Professional.



#### Basic:

- + Free download from App Store and Google Play
- + Auto-connect to the instrument
- + Remotely display instrument measurements
- + Set target values
- + View multiple measurements simultaneously
- + Supports multiple languages
- + Display measurements in Imperial or metric units



#### **Advanced - Includes Basic Functionality Plus:**

- + Subscription-based feature set
- + Connect up to 2 instruments for simultaneous, real-time display and data logging
- + Perform flow rate calculations based on user-input duct size or K-factor
- + Log measurements to smart device
- + Export data with comments and photos for report generation



# Professional - Includes Basic and Advanced Functionality Plus: —

- + Subscription-based feature set
- + Connect up to 6 instruments for simultaneous, real-time display and data logging
- + Built in duct traverse workflow supporting both Equal Area and log-Tchebycheff test methods
- + Supports an optional SD card for use in long- or short-term unattended data logging applications

	AirPro Feature Sets		
Function	Basic	Advanced (1 Year/Long-Term)	Professional (1 Year/Long-Term)
Display Multiple Measurements Simultaneously	X	Х	X
Supports Multiple Languages	Х	X	Х
Configure For Imperial or Metric Units of Measurements	X	Х	X
Calculate Pitot Probe Velocity	X	X	Х
Standard or Actual Velocity Calculation	Х	Х	Х
Max # of Instruments Connected to AirPro Mobile Simultaneously	1	2	6
Volumetric Flow Rate Calculation (Kf or Pitot Probe)		X	X
Statistics		X	Х
Data Logging		X	X
Export Data		X	Х
Enable Utilization of Instruments SD Card Slot for Data Storage			Х
Graphing			X
Duct Traverse Application			Х
Online Access to Calibration Certificates			Х









# AIRPRO MICROMANOMETER MODEL AP800 AND ACCESSORIES

#### Model AP800 Includes: —

Instrument, calibration certificate, quick start guide, universal AC/DC adapter, battery, service and registration cards.



#### **Carrying Case**

Small carrying case; capable of holding 1 meter, 1 probe,

3 extensions plus accessories

800535 Large carrying case; capable of holding 2 meters, 2 probes,

3 extensions plus accessories



#### Static Pressure Probes and Tubing Kit

800533 Static Pressure Probes and Tubing Kit; contains two static

pressure probes and two 4 ft. (1.2 m) lengths of tubing



#### Pitot Probes -

634634000	Pitot probe (5/16" (8 mm) diameter) - 12" (30 cm)
634634001	Pitot probe (5/16" (8 mm) diameter) - 18" (46 cm)
634634002	Pitot probe (5/16" (8 mm) diameter) - 24" (61 cm)
634634003	Pitot probe (5/16" (8 mm) diameter) - 36" (91 cm)
634634005	Pitot probe (5/16" (8 mm) diameter) - 60" (152 cm)

634634004 Telescoping pitot probe - 8" to 38" (20 cm to 96 cm)



#### Miscellaneous -

800530 External battery charger

634650002 Duct plug, 3/8" (9.5 mm) diameter - 1000 pieces 634650003 Duct plug, 3/8" (9.5 mm) diameter - 5000 pieces





#### **SPECIFICATIONS**

### AIRPRO® MICROMANOMETER INSTRUMENTS MODEL AP800 AND ACCESSORIES

#### Static / Differential Pressure

-15 to +15 in. H<sub>2</sub>0 Range<sup>1</sup>

(-28.0 to +28.0 mm Hg, -3735 to +3735 Pa)

Accuracy  $\pm 1\%$  of reading  $\pm 0.005$  in. H<sub>2</sub>O

 $(\pm 0.01 \text{ mm Hg}, \pm 1 \text{ Pa})$ 

Resolution 0.001 in.  $H_2O$  (0.1 Pa, 0.01 mm Hg)

#### **Velocity (Pitot Probe)**

250 to 15500 ft/min (1.27 to 78.7 m/s) Range<sup>2</sup> Accuracy<sup>3</sup> ±1.5% at 2000 ft/min (10.16 m/s)

Resolution 1 ft/min (0.1 m/s)

#### Barometric Pressure (AP800)

20.36 to 36.65 in. Hg (517.1 to 930.9 mm Hg) Range

Accuracy ±2% of reading

#### **Instrument Temperature Range**

Operating 40 to 113°F (5 to 45°C) Storage -4 to 140°F (-20 to 60°C)

#### **Display interface**

Organic light-emitting diode (OLED) 0.4 in. (10 mm) digit height

#### **External Meter Dimensions**

2.1 in. x 7.1 in. x 1.6 in. (53 mm x 181 mm x 40 mm)

#### **Meter Weight**

Weight with batteries: 0.45 lbs (0.20 kg)

#### **Power Requirements**

AirPro Li-ion battery 3500 mAh

AC Adapter (TSI part number 800531 only) Input 90 to 240 VAC, 50 to 60 Hz

5 VDC, 2A Output

#### **Battery Life**

32+ hours

Specifications are subject to change without notice.

Bluetooth is a registered trademark owned by the Bluetooth SIG, Inc.

AirPro, TSI and the TSI logo are registered trademarks of TSI Incorporated.



**TSI Incorporated** - Visit our website **www.tsi.com** for more information.

Tel: +1 800 874 2811 Tel: +91 80 67877200 USA India UK Tel: +44 149 4 459200 Tel: +86 10 8219 7688 China Tel: +33141192199 Singapore Tel: +65 6595 6388 France Germany Tel: +49 241 523030

P/N 5001805 Rev D ©2017 TSI Incorporated Printed in U.S.A.

<sup>&</sup>lt;sup>1</sup> Overpressure range = 7 psi (190 in. H20, 360 mmHg, 48 kPa).

<sup>&</sup>lt;sup>2</sup> Pressure velocity measurements are not recommended below 1,000 ft/min (5 m/s).

<sup>&</sup>lt;sup>3</sup> Accuracy is a function of converting pressure to velocity. Conversion accuracy improves when actual pressure values increase