## Sapphire Infrared Transmitter IRT-55









Sapphire Pendant infrared transmitter/microphone with rechargeable Lithium-ion battery and unidirectional microphone for true voice reproduction and excellent feedback suppression.

	Specifications		Features
(	Transmitter Carrier	Infrared	• Elegant Design
	Transmission Frequencies	2.08 MHz and 2.54 MHz	<ul> <li>Only 1.4 oz. including battery</li> </ul>
	Channel Switchable A or B	Field Switchable	<ul> <li>Long life "Lithium ion" battery</li> </ul>
	Transmitting Diodes	Six	Rechargeable via micro USB cable
	Modulation	FM Wide-Band	Battery level indicator
	Pilot Tone Frequency	32.768 KHz	-Back light under power switch
	Peak Deviation	± 25KHz	• Momentary mute button,
	Operating Range	1,500 Ft <sup>2</sup> . 60 Ft. Line of Sight	Backlight blinks in mute mode
	Battery Discharge Indicator		<ul> <li>Push "on/off" power</li> </ul>
	Blue	Full	• Channel A or B selectable
	Purple	Medium	<ul> <li>Three level mic volume switch</li> </ul>
	Red	Low	(low, medium, high)
	Flashing Red	Very Low Battery	• Auxiliary input (3.5mm)
	Battery Used	Lithium-ion (3.7V / 620mAh)	<ul> <li>Low profile clip for mounting</li> </ul>
	Battery Life	Approx. 8-9 Hrs/Charge	<ul> <li>Wear with a lanyard or directly to neckline collar</li> </ul>
	External Power Charger	DC +5V, Micro USB Connector	
	Transmission Angle	180° Conical	
	User Controls		
	Power Switch (Push)	On/Off	
	Mute Switch (Push)	On/Off	
	Mic Switch (3 position)	+ 6db, Normal, - 3db	Touchboards
	Aux. Vol/Gain	Increase, Decrease	
	Channel Select	(A or B) in battery compartment	205 Westwood Ave, Long Branch, NJ 07740
	External Aux Input	3.5mm Stereo Line Level	Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088   E-mail: sales@touchboards.com
	Dimensions ( $H \times W \times D$ )	3 in x 1 ¼ in x ¾ in	······ (····· ) · · · · · · · · · · · · · ·
	Weight	1.4 oz including battery	
1			

