

Wall-Mount Speaker SP-2000



SP-2000 Wall-mount/book shelf speaker, two-way, 8 Ω , mounting bracket. White.

Specifications

Frequency Range	80 Hz to 16 kHz, \pm 6dB
Power	30 watts Continuous
Sensitivity	88 dB SPL
Impedance	8 Ω
Crossover Frequency:	6 kHz
Nominal Coverage	90° x 90°
LF Driver	(5.25 in) Polycarbonate / rubber
HF Driver	High efficient 1" Mylar domed tweeter
Enclosure Material	Structural reinforced ABS enclosure with metal mesh grille
Termination	Spring terminal for secure speaker wire connection
Dimensions (H x W x D)	5.5 x 7.25 x 4.25 in
Net Weight (ea)	5 lbs 2 oz
Shipping Weight (pr)	10 lbs 9 oz
Included Accessories	Wall mount bracket

Features

- Two-way speaker,
 - 6" woofer and a high efficient 1" mylar domed tweeter
 - Passive crossover
 - Housed in a ported enclosure
 - Shielded magnet to prevent video interference
- Frequency Response: 80 Hz–16,000 Hz, \pm 6dB
- Impedance: 8 Ω
- Power Handling: 30 watts Continuous
- Structural reinforced ABS enclosure with metal mesh grille
- Mounting bracket for wall-mount or desk top stance
- Spring terminal for secure speaker wire connection
- White Color

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com