

Titan^{neo} Portable PA-800



Titan AC/Battery powered portable sound system (basic unit). The Input Panel provides a Lo-z XLR Microphone Input with Volume Control, Stereo Line Input with volume control and Dual Line Output, Treble & Bass Controls, Master Volume Control. Voice Priority Circuit and Battery Level Indicator.

Specifications

Output Power	50 W RMS, 80 W Max
Sensitivity	91dB, 1W @ 1M
Maximum SPL	95 dB
Frequency Response	20 Hz - 20 kHz (audio)
Speaker	8" LF Neodymium Woofer 1" HF Horn
Signal to noise Ratio	>70dB
Audio Input	XLR-TRS Balanced Mic Line Level, Dual RCA
Audio Output	Line Level, Dual RCA
Controls	Master Volume, Treble, Bass Mic Vol.
Rechargeable Battery Type	Two 12 VDC / 4.1 AH, NiMH
Operating Life	About 6-8 hours
Charging Time	About 8-10 hours
Power Supply	100-240 V AC Input European Approval
Dimensions	11 3/4" W x 18 1/2" H x 9" D
Weight	21 lbs.

Features

- New Auto Scan UHF Wireless Module
- New Neodymium LF Speaker
- New Nickel Metal Hydride batteries
- New Four stage battery level indicator
- Light Weight
- Durable high impact enclosure
- Efficient two-way speaker system
- Simultaneous mixing with the microphone inputs
- Plug-In microphone Lo-z, XLR Connection
- Treble and bass controls
- Dual line input and output (RCA)
- Rechargeable Nickel Metal Hydride batteries for an extended 6-8 hours of continuous use
- AC Operable without batteries being fully charged
- AirLink transmitter for wireless transmission of program to powered companion speaker
- Voice Priority Switch
- Can be upgraded to include up to two Wireless Auto Scan
- Receiver, Wireless Transmitter & CD/MP3 Player
- AirLink Router and Spartan compatible