



Wall Mount Speaker SP-2000

Two-way wall-mount/book shelf speaker

Specifications

Frequency Range	80 Hz - 16 kHz, ± 6 dB
Power	30 W continuous
Sensitivity	88 dB SPL
Impedance	8 Ω
Crossover Frequency:	6 kHz
Nominal Coverage	90° x 90°
LF Driver	5.25 in polycarbonate / rubber
HF Driver	High-efficiency 1" Mylar domed tweeter
Enclosure Material	Structural reinforced ABS enclosure with metal mesh grille
Termination	Spring terminal for secure speaker wire connection
Dimensions	5.5" H x 7.25" W x 4.25" D
Net Weight (ea)	4 lb 3 oz
Shipping Weight (pr)	10 lb 9 oz
Included Accessories	Wall mount bracket

Features

- Two-way speaker
 - 5.25" woofer and a high efficient 1" Mylar domed tweeter
 - Passive crossover
 - Housed in a ported enclosure
 - Shielded magnet to prevent video interference
- Frequency Response: 80 Hz–16,000 Hz, ± 6 dB
- Impedance: 8 Ω
- Power Handling: 30 W Continuous
- Structural reinforced ABS enclosure with metal mesh grille
- Mounting brackets for wall-mount or bookshelf
- Spring terminal for secure speaker wire connection
- Color: white