

Speakers



Lay-In Speaker SP-628L

SP-628L 2-Way, Lay-in Ceiling Speaker Assembly

Specifications

| | |
|----------------------------|---|
| Frequency Range | 120 Hz to 21 kHz, \pm 6 dB |
| Power | 30 Watts Continuous |
| Sensitivity | 87 dB SPL (1W/1M) |
| Impedance | 8 Ω |
| Nominal Coverage | 90° x 90° |
| LF Driver | 6.5" Cone Driver |
| Magnet | 10 oz |
| HF Driver | High efficiency 1" domed tweeter |
| Enclosure Material | Air Sealed Metal Backcan |
| Termination | Screw terminals for secure speaker wire connection |
| Mounting | Attached "T" Bar support |
| Dimensions (H x W x D) | 12.25" x 23.75" x 6.25" (13" with "T" Bar support) |
| Net Weight (ea) | 8 lb |
| Shipping Weight (box of 4) | 39 lb |
| UL Requirement | Meets UL 2043 criteria for plenum installation |

Features

- Complete speaker assembly (12" X 24")
- Perforated steel grill
- Heavy duty support for anti rattle or movement
- Attached adjoining T-bar
- Air Sealed Metal Back Can for an infinite baffle
- Screw terminal
- 3 pre-installed brackets for safety wire
- Completely painted, tile white
- No speaker assembly required
- Quick and efficient installation