



# Wall Mount Speaker SP-2000

Two-way wall-mount/book shelf speaker

## Specifications

Frequency Range	80 Hz - 16 kHz, $\pm 6$ dB
Power	30 W continuous
Sensitivity	88 dB SPL
Impedance	8 $\Omega$
Crossover Frequency:	6 kHz
Nominal Coverage	90° x 90°
LF Driver	5.25 in polycarbonate / rubber
HF Driver	High-efficiency 1" Mylar domed tweeter
Enclosure Material	Structural reinforced ABS enclosure with metal mesh grille
Termination	Spring terminal for secure speaker wire connection
Dimensions	5.5" H x 7.25" W x 4.25" D
Net Weight (ea)	4 lb 3 oz
Shipping Weight (pr)	10 lb 9 oz
Included Accessories	Wall mount bracket

## Features

- Two-way speaker
  - 5.25" woofer and a high efficient 1" Mylar domed tweeter
  - Passive crossover
  - Housed in a ported enclosure
  - Shielded magnet to prevent video interference
- Frequency Response: 80 Hz–16,000 Hz,  $\pm 6$  dB
- Impedance: 8  $\Omega$
- Power Handling: 30 W Continuous
- Structural reinforced ABS enclosure with metal mesh grille
- Mounting brackets for wall-mount or bookshelf
- Spring terminal for secure speaker wire connection
- Color: white