

# Routine Laboratory Thermoregulators

## Baths and Thermoregulators

### Technical Specification

<b>Specifications to DIN 12876</b>	<b>TE-10A</b>	<b>TE-10D</b>
Temperature range*	-20°C to +95°C	-40°C to +120°C
Temperature selection	Analogue	Digital
Temperature stability using water @ 40°C	±0.01°C	±0.01°C
Method of control	Proportional	PID
Temperature sensor	Thermistor	PRT
Adjustable over-temperature cut-out	Yes	Yes
Low liquid level cut-out	Yes	Yes

### Heating/Pumping

Pump capacity litres/minute	10	10
Pump capacity (mbar)	145	145
Nominal heater power at 120V (W)	1000	1000
Nominal heater power at 240V (W)	1000	1000
Extension below base, mm	145	145
Dimensions (L x W x H), mm	237 x 124 x 260	237 x 124 x 260
Shipping Weight, kg	3.7	3.9

\* Refrigeration or cooling coil required for below ambient cooling  
(see Techne Flow and Dip Coolers and the cooling coil).

### Ordering Information

<b>Description</b>	<b>Product codes</b>		
	<b>230V</b>	<b>120V</b>	<b>100V</b>
TE-10A, analogue thermoregulator, -20°C to 95°C, (supplied with clamp)	FTE10ADC	FTE10APC	FTE10AYC
TE-10D, digital thermoregulator, -40°C to 120°C, (supplied with clamp)	FTE10DDC	FTE10DPC	FTE10DYC