Baths and Thermoregulator



Four bath capacities – 8, 12, 18 and 26 litre

• Stainless steel construction

to hold the thermoregulator.

Unheated Baths

• Seam-free and corrosion resistant stainless steel inners for easy cleaning

Designed to be used with a clip-on Tempette or Tempunit® thermoregulator, these baths incorporate carrying handles for added safety. All baths have stoved enameled steel outer cases and are supplied with bridge mounting plate

- Rugged splash-proof case
- Integrated carrying handle
- Maximum working temperature of 200°C
- All models come with a 3 year warranty as standard



48 litre

- 48 litre capacity
- Welded construction
- All submerged parts are made from stainless steel
- Rugged splash-proof case
- Maximum working temperature of 200°C



Technical Specifactions

Capacity litres		8	12	18	26	48
Dimensions (mm)	Length	265	354	530	530	594
	Width	325	325	325	325	365
	Height	172	172	172	222	298
Internal Dimensions	Length	240	329	505	505	559
(mm)	Width	300	300	300	300	330
	Height	150	150	150	200	274
Top of bath to liquid	level					
max depth (mm)		65	65	65	65	65
Working length to						
thermoregulator (mm)		115	205	380	380	430
Working depth -						
max/min (mm) Working capacity -		130/100	130/100	130/100	180/150	255/224
max/min (litres)		8.0/6.0	11.6/8.4	18.0/13.2	26.0/20.5	8.5/42.5
		5.5kg	6.1kg	7.5kg	9.5kg	14.6kg
Shipping Weight		3.3Kg	o. rkg	7.5kg	9.5kg	14.0Kg

For temperatures up to 250°C we recommend the use of the LCB range of baths.



Ordering Information

Product Code	Description
FBATH08	B-8 stainless steel bath, 8 litre capacity
FBATH12	B-12 stainless steel bath, 12 litre capacity
FBATH18	B-18 stainless steel bath, 18 litre capacity
FBATH26	B-26 stainless steel bath, 26 litre capacity
FBATH48	B-48 stainless steel bath, 48 litre capacity