

TECHNI-PRO

Product Data Sheet

ESD Safe “Rejected” Tag with String

10065613

REJECTED STATIC DISSIPATIVE 

Job No. _____ PO No. _____

Part Number _____ Serial No. _____

Part Name _____

Number of Pieces Rejected _____

Reason _____

Disposition _____

Inspector _____ Date _____



Key Features:

- Keep track of printed circuit boards or sub-assemblies
- Permanently static dissipative
- Not dependent on humidity
- Recyclable
- Paper stock has stiff surface and easy to write on
- Cotton string attached to tie on to your application

Product Specifications:

Dimensions: 2.75" x 5"

Color: Red

Legend: Rejected

ESD-Safe: Yes

Packaging: 50/Package

Rev. MAY23

TECHNI-PRO

Production supplies that **WORK** as hard as you do

Techni-PRO is a TestEquity private label brand featured on:

www.testequity.com/brand/techni-pro
www.techni-tool.com/brand/techni-pro
www.jensentools.com/brand/techni-pro

Technical data

Electrical

Two thickness (calipers) offered: 0.0040" and 0.0080"

Typical Test Data - Physical:

Base weight (3000 sq. ft.)	20#	40#
Thickness (+ - 0.0005")	0.004" (0.097mm)	0.0080" (0.2mm)
Resistivity (@ 15% RH at 10 Volts AP)	2.9×10^{10}	7.0×10^9
Resistivity (@ 15% RH at 100 Volts AP)	2.2×10^{10}	3.0×10^9
Resistivity (@ 50% RH at 10 Volts AP)	2.7×10^8	5.1×10^7
Resistivity (@ 50% RH at 100 Volts AP)	2.3×10^8	4.3×10^7

Typical Test Data - Chemical:

pH (acid level)	7.02 (neutral)
Chloride (Cl)	< 100 ppm
Nitrate (NO ₃)	< 10 ppm
Amine (NH ₂ – R)	< 55 ppm
Sodium (Na)	< 85 ppm
Shelf Life (Minimum)	5 years

Not subject to RoHS-guidelines (2002/95/EG and 2002/96/EG)

The Environment

Paper and tags can be re-used multiple times without loss of electrical properties.

Can be also be recycled in the regular wastepaper stream.

Rev. MAY23