



## E-Line Contact Cleaner Product# 1622

### Product Description

Hydrocarbon based defluxer formulated to be powerful, yet very economical. Eliminates brushing and scrubbing, saving time and materials. Clean oxidation, oil, and other contaminants from contacts, metal switches, relays, edge connectors, buss bars, and circuit breakers.

### Features / Benefits

- Powerful cleaner
- Ideal for sensitive plastics
- Low toxicity
- Non-ozone depleting
- Zero residue

### Usage Instructions

Disconnect equipment from power source. Hold can 6-8 inches away. When used as a general cleaner, start at top of area to be cleaned using a sweeping motion and spray the area, slowly working toward the bottom. To clean in hard to reach areas, insert extension tube in sprayhead. Allow components to dry completely before applying current.

### Plastics & Rubber Compatibility

MATERIAL NAME	RATING
ABS:	Excellent
Nylon:	Excellent
Lexan:	Excellent
HDPE:	Excellent
LDPE:	Excellent
C.E. Phenolic:	Excellent
PMMA:	Excellent
POM:	Excellent
PP:	Excellent
PS:	Excellent
PTFE:	Excellent
PVC:	Excellent



### Typical Product Data and Physical Properties

<b>Physical state:</b>	Liquid
<b>Color:</b>	Clear, colorless
<b>Odor:</b>	Characteristic
<b>Vapor pressure:</b>	7.4 kPa (55.5 mmHg)
<b>Volatility:</b>	100% (w/w)
<b>Evaporation rate:</b>	>1 ((TCE=1) =1)
<b>Aerosol product</b>	
<b>Type of aerosol:</b>	Spray
<b>Heat of combustion:</b>	30.26 kJ/g
<b>Shelf life:</b>	5 years

## E-Line Contact Cleaner Product# 1622

### Packaging and Availability

---

1622-10S	10 oz. Aerosol (284g)
1622-13S	13 oz. Aerosol (369g)

### Environmental Policy

---

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

### Resources

---

Techspray® products are supported by global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email [tsales@techspray.com](mailto:tsales@techspray.com) or visit our web site at: [www.echspray.com](http://www.echspray.com).

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.