



Eco-Freezer

Product# 1583

Product Description

Eco-Freezer is formulated with new HFO-1234ze propellant; with a fraction of the global warming potential (GWP) of HFC-134a based freeze sprays. HFO-1234ze has a GWP of 6, compared to HFC-134a with GWP of 1300. Eco-Freeze can be a drop-in replacement when GWP needs to be lowered.

Features / Benefits

- Global Warming Potential (GWP) of <1
- Chills down to -49°F (-45°C)
- Nonflammable*
- Non-ozone depleting
- Zero residue & no odor

* under ambient conditions

Applications

- Cool Equipment for testing
- Dissipate heat while soldering or desoldering
- Isolate thermal intermittent components
- Test circuit traces for continuity
- Test printed circuit boards for stress fractures
- Track intermittent failures and shorts

Usage Instructions

CAUTION: Always be sure that sprayhead is aimed at surface to be chilled. Allow components to heat up to normal operating temperature or until intermittent fault occurs. Spray suspected component until chilled. Product will freeze small areas. Due to the colder temperature and the more aggressive nature of the product, it is possible that prolonged spraying may cause blistering of some conformal coatings or deterioration of some plastics. Always test on an inconspicuous area before using. Can crack ceramics and other temperature sensitive components.



Typical Product Data and Physical Properties

Physical state	Gas
Flash Point	Product does not sustain combustion
Auto-ignition temperature	694.4°F (368°C)
Color	Clear, colorless
Odor	Ethereal; Faint odor
Boiling/condensation point	-2.2°F (-19°C)
Vapor pressure	8kPa (60 mmHg) room temperature
Shelf life	10 years

Eco-Freezer

Product# 1583

Compatibility

Material	Compatibility
Buna-N	Excellent
Graphite	Excellent
HDPE	Excellent
LDPE	Excellent
Lexan	Excellent
Neoprene	Excellent
Cross-Linked PE	Excellent
Polyacrylate	Excellent
Polystyrene	Excellent
PVC	Excellent
Silicone Rubber	Excellent
Teflon	Excellent
Viton	Excellent

Environmental Impact Data

CFC	0.0%
HCFC	0.0%
CL Solv.	0.0%
VOC	0.0%
HFC	0.0%
ODP	0.0

Packaging and Availability

1583-10S 10 oz. (284g)

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray® products are supported by global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.echspray.com.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.