



TLC-1000-U2S

USB2.0

HD PTZ Video Camera

Telycam TLC-1000-U2S is cost effective 10X USB2.0 HD video conferencing PTZ camera for web conferencing and video conferencing, to offer enterprise-class image and flexible control.



FEATURES

- ◆ Adopted advanced industrial level ISP, and Sony 5MP CMOS sensor, to output crisp image
- ◆ Full HD 1080p/30 resolution
- ◆ WDR, BLC, 3D noise reduction and exposure compensation value to be adjustable via OSD menu with applied environment
- ◆ Fast&accurate focus and 10x lossless optical zoom, with 62.5 degree wide angle FOV, along with smooth pan/tilt rotation to capture any view in conferencing space
- ◆ Plug&PlayUSB2.0 video streaming output, compatible with most leading video conferencing software: Zoom.us, Skype4business, Vidyo, Bluejeans, Webex, Google Hangout, Trueconf, Gotomeeting ect, at different operation system Windows, Mac, Android and Linux. ect, at different operation system Windows, Mac, Android and Linux."
- ◆ FECC (Far End Camera Control) supported
- ◆ Standard Visca and UVC1.5 Protocol
- ◆ PTZ control and firmware upgrade via RS232 (RS485) and USB
- ◆ 128 presets.



Telecam Technology Co.,Ltd
 New Add.: 6F, Building A, Shuanguan Information Technology Industrial Park, No.8,
 Baoqing Rd, Longgang District, Shenzhen, 518116, China
 TEL: 0086-755-33275155 Http://www.telycam.com www.telecamtech.com

TECHNICAL SPEC

Camera			
Sensor	1/2.8 inch high quality 5MP HD CMOS sensor		
Frame Rate	1920x1080p30/25, 1280x720p60/50/30/25		
Video Format	MJPEG		
Lens Zoom	10x optical zoom		
Focal length	f=4.7 (wide)~47mm(tele)		
View Angle	6.43° (wide) ~ 62.5° (tele)		
SNR	>50dB		
Noise Reduction	2D/3D		
Minimum Lux	0.1 lux		
White Balance	Auto / Manual		
Focus	Auto / Manual		
Iris	Auto / Manual		
Electronic Shutter	Auto / Manual		
BLC	Auto / Manual		
Mechanism			
Pan Rotation Angle	-170° ~ +170°	Tilt Rotation Angle	-35° ~ +90°
Pan Rotation Speed	0°~120°/s	Tilt Rotation Speed	0°~80°/s
Preset	128 presets via RS232, 10 presets via remote controller		
Control	RS232/RS485/USB/Remote Controller		
Video Port	USB2.0		
Input voltage	DC12V		

Camera Dimension

148mm×132mm×161mm

Package Dimension

28x24x24cm

Package Content

Camera, Remote Controller
RS232 cable, USB2.0 cble,
Power Supply

