



TLC-1000-U3S

USB3.0

HD PTZ Video Camera

Telycam TLC-1000-U3S Smart and affordable USB3.0 HD Video Conferencing Camera, ideal for huddle room, specially corporation, telemedicine, on-line education and other professional cloud-based unified communication



FEATURES

◆ Adopted advanced industrial level ISP , Sony 1/2.8 5MP sensor, output full HD 1080p with 60 frames per second video streaming, to offer you completely high definition, noiseless and crisp,realistic color image with full details

- ◆ Using multi-element 10x lossless optical zoom lens, with 62.5 degree wide angle FOV, along with smooth pan&tilt rotation and fast&accurate focus to capture any view in conferencing space
- ◆ USB3.0 Output, Plug-and-Play, Standard UVC1.5 protocol enable users to connect camera with PC by a single USB cable
- ◆ Compatible with most leading video conferencing software and platform: Zoom.us, Skype4business, Vidyo, Bluejeans, Webex, Google Hangout, Trueconf, Gotomeeting ect, at different operation system Windows, Mac, Android and Linux
- ◆ And FECC (far-end camera control) supported
- ◆ Standard Sony Visca and UVC1.5 protocol, PTZ control and firmware upgrade via RS232 (RS485) and USB port
- ◆ 128 presets supported
- ◆ Support multiple mount way: available to install on desk, monitor, tripod or up-side down in-ceiling



Telecam Technology Co.,Ltd
 New Add.: 6F, Building A, Shuanguan Information Technology Industrial Park, No.8,
 Baoqing Rd, Longgang District,Shenzhen,518116,China
 TEL: 0086-755-33275155 Http://www.telycam.com www.telecamtech.com

TECHNICAL SPEC

Camera			
Sensor	1/2.8 inch high quality 5MP HD CMOS sensor,		
Video System	1920x1080p60/50/30/25, 1280x720p60/50/30/25		
Video Format	YUY2		
Lens Zoom	6.43° (wide) ~ 62.5° (tele)		
SNR	>50dB		
Noise Reduction	2D/3D		
Minimum Lux	0.1 lux		
White Balance	Auto / Manual		
Focus	Auto / Manual		
Iris	Auto / Manual		
Electronic Shutter	Auto / Manual		
BLC	Auto / Manual		
Mechanism			
Pan Rotation Angle	-170° ~ +170°	Tilt Rotation Angle	-35° ~ +90°
Pan Rotation Speed	0°~120°/s	Tilt Rotation Speed	0°~80°/s
Preset	128 presets via RS232, 10 presets via remote controller		
Control	RS232/RS485/USB/Remote Controller		
Video Port	USB3.0		
Lens Zoom	10x optical zoom		
Input voltage	DC12V		

Camera Dimension

148mm×132mm×161mm

Package Dimension

28x24x24cm

Package Content

Camera, Remote Controller,
RS232 cable, USB3.0 cble,
Power Supply

