

TLC-300-U2S USB2.0

HD PTZ Video Camera

Telycam TLC-300-U2S is an affordable price as well as professional quality USB2.0 HD PTZ Video Conferencing Camera, sensible choice for cost effective unifed video collaboration solution



FEATURES |

- Adopted advanced American Ambarella ISP, and Sony 5MP CMOS sensor, to output crisp image
- ◆ Full HD 1080p/30 resolution
- ♦ WDR, BLC, 3D noise reduction and exposure compesation value to be adjustable via OSD menu with applied environment

- ◆ Fast&accurate focus and 12x lossless optical zoom, with 72.5 degree wide angle FOV, along with smooth pan/tilt rotation to capture any view in conferencing space
- Plug&Play,USB2.0 video streaming output, compatible with most leading video conferencing software: Zoom.us, Skype4business, Vidyo, Bluejeans, Webex, Google Hangout, Trueconf, Gotomeeting ect, at different operation system Windows, Mac, Android and Linux
- ◆ FECC (Far End Camera Control) supported
- ♦ PTZ control and firmare upgrade via RS232 (RS485) and USB
- 128 presets
- Support multiple mount way: available to install on desk, monitor, tripod or up-side down in-ceiling



TLC-300-U2S USB2.0 HD PTZ Video Camera



TECHNICAL SPEC

Sensor	1/2.8 inch high quality 5MP HD CMOS sensor	Frame Rate	1920x1080@30, 1280x720@30, 640x480@30
Video Format	MJPG	Lens Zoom	12x optical zoom
Focal length	f=3.92(wide)~47.32mm(tele)	View Angleh	6.3° (wide) ~ 72.5° (tele)
SNR	>50dB	Noise Reduction	2D/3D
Minimum Lux	0.1 lux	White Balance	Auto / Manual
Focus	Auto / Manual	Iris	Auto / Manual
Electronic Shutter	Auto / Manual	BLC	Auto / Manual
Mechanism			
Pan Rotation Angle	-170° ~ +170°	Tilt Rotation Angle	-35° ~ +90°
Pan Rotation Speed	0°~120°/s	Titl Rotation Speed	0°~80°/s
Preset	128 presets via RS232, 10 presets via remote controller	Control	RS232/RS485/USB/Remote Controller
Video Port	USB2.0	Input voltage	DC12V

Camera Dimension 220mm×173mm×117mm

Package Dimension 32x30x31cm

Package Content Camera, Remote Controller, RS232 cable, USB2.0 cble, Power Supply







