



# TLC-300-U3S USB3.0 HD PTZ Video Camera

Telycam TLC-300-U3S Enterprise-class USB3.0 PTZ Video Conferencing Camera , positioning for middle and large meeting room video communication



## FEATURES

- ◆ Adopted Ambarella ISP, Sony 1/2.8 5MP sensor, output full HD 1080p with 60 frames per second video streaming, to offer you completely high definition, noiseless and crisp, realistic color image with full details
- ◆ using multi-element 12x lossless optical zoom lens, with 72.5 degree wide angle FOV, along with smooth pan&tilt rotation and fast&accurate focus to capture any view in conferencing space

- ◆ USB3.0 Output, Plug-and-Play, standard UVC1.5 protocol enable users to connect camera with PC by a single USB cable
- ◆ compatible with most leading video conferencing software and platform, Zoom.us, Skype4business, Vidyo, Bluejeans, Webex, Google Hangout, Trueconf, Gotomeeting ect, at different operation system Windows, Mac, Android and Linux
- ◆ Standard UVC1.5 protocol enable users to connect camera with PC by a single USB cable
- ◆ FECC (far-end camera control) supported
- ◆ Standard Sony Visca and UVC1.5 protocol, PTZ control and firmware upgrade via RS232 (RS485) and USB port
- ◆ 128 presets supported
- ◆ Support multiple mount way: available to install on desk, monitor, tripod or up-side down in-ceiling



Telecam Technology Co.,Ltd  
 New Add.: 6F, Building A, Shuanghuan Information Technology Industrial Park, No.8,  
 Baoqing Rd, Longgang District, Shenzhen, 518116, China  
 TEL: 0086-755-33275155 Http://www.telycam.com www.telecamtech.com

# TLC-300-U3S

## USB3.0

### HD PTZ Video Camera



## TECHNICAL SPEC

<b>Sensor</b>	1/2.8 inch high quality 5MP HD CMOS sensor,		
<b>Video System</b>	1920x1080p60/50/30/25, 1280x720p60/50/30/25		
<b>Video Format</b>	YUY2	<b>Lens Zoom</b>	12x optical zoom
<b>Focal length</b>	f=3.92(wide)~47.32mm(tele)	<b>View Angle</b>	6.3° (wide) ~ 72.5° (tele)
<b>SNR</b>	>50dB	<b>Noise Reduction</b>	2D/3D
<b>Minimum Lux</b>	0.1 lux	<b>White Balance</b>	Auto / Manual
<b>Focus</b>	Auto / Manual	<b>Iris</b>	Auto / Manual
<b>Electronic Shutter</b>	Auto / Manual	<b>BLC</b>	Auto / Manual
<b>Pan Rotation Angle</b>	-170° ~ +170°	<b>Tilt Rotation Angle</b>	-35° ~ +90°
<b>Pan Rotation Speed</b>	0°~120°/s	<b>Tilt Rotation Speed</b>	0°~80°/s
<b>Preset</b>	128 presets via RS232, 10 presets via remote controller	<b>Control</b>	RS232/RS485/USB/Remote Controller
<b>Video Port</b>	USB3.0	<b>Input voltage</b>	DC12V

Camera Dimension  
220mm×173mm×117mm

Package Dimension  
32x30x31cm

Package Content

Camera, Remote Controller,  
RS232 cable, USB3.0 cable,  
Power Supply

