

Thermo Scientific Digital Bottle/Tube Roller

Maximize valuable bench space with our compact, adjustable speed unit, capable of rolling multiple tube and bottle sizes

- Adjustable speed accommodates a variety of applications
- Anti-corrosive and wear resistant construction enables use in humid and CO₂ environments
- Adjustable rollers accommodate a variety of tube/bottle sizes
- Stacking kit allows you to stack units two high, saving valuable bench space
- Optional remote control facilitates operating unit while in incubator and adds timer function
- Includes O Rings for smooth rolling of 15 or 50ml tubes

Common Applications

- Cell Culture
- Hybridization Assays
- Liquid Mixing
- Bioproduction



Nalgene Unwire Test Tube Full Rack

Cat. No.	88881003	88881004
Plug configurations		
Roller Speed	1-80rpm	
Maximum Bottle Diameter	≤ Φ 120mm / 4.72in	
Number of Rollers	6 rollers standard, up to 11 can be added	
Roller Dimensions (D x L)	Φ 28 x 259mm / 1.1 x 10.2in	
Display	LED Roller Speed Display	
Timing Range (optional control box needed)	0-999min or continuous	
Stackable	Two high with optional kit	
Maximum Working Capacity	6.5kg / 14.3lbs	
Maximum Power	10W	
Operating Temperature	4°C – 60°C	
Relative Humidity Tolerance	≤ 95%	
Dimensions W x L x H	378 x 360 x 72mm / 14.9 x 14.2 x 2.8in	
Weight	6.5kg / 14.3lbs	
Power	AC100V-240V / 50Hz 60Hz	
Certification	CE cCSAus	
Warranty	2 year	

Accessories for Bottle/Tube Roller	Cat. No.
Additional Rollers (pack of two)	88881010
O ring for 50ml tube (pack of 20) 23.5 x 3.55mm .93 x .14in	88881011
O ring for 15ml tube (pack of 20) 13.2 x 2.65mm .52 x .1in	88881012
Bar for stacking (pack of four)	88881013
Remote Control	88881014

Note: Two bottle rollers stacked reach 32cm in height.

