

Thermo EIG750 - Heratherm Incubation Chamber 750L Specifications

Alarm Types: Audible and Visible

Capacity (English): 26.5cu.ft.

Capacity (English) Shelf: 66.1lbs

Capacity (Metric) Shelf: 30kg

Certifications/Compliance: UL, CE

Data Outputs: USB, Ethernet

Capacity (Metric): 750L

Chamber Material: Powder-coated Cold Rolled Steel

Lighting: No

Material: Powder-coated Cold Rolled Steel

No. of Shelves: 3

Plug Type: Nema 5-20P

Relative Humidity: 10 to 90%

Temperature Range (Metric): 0 to 70°C

Type: Environmental Chamber

Display: 7 in. touchscreen user interface

Door Style: Glass door

No. of Casters: 4

Ports: 2 access ports

Programmability: Temperature ramping

Resolution: 0.1°C

Shelf Area (English): 4.9ft²

Shelf Area (Metric): 0.46m²

Shelf Material: Stainless Steel (304/1.4301)

Temperature Control: Microprocessor - programmable

Temperature Stability: $\leq \pm 0.1^{\circ}\text{C}$ @ 20°C to 37°C

Temperature Uniformity: $\leq \pm 0.5^{\circ}\text{C}$ @ 20°C to 37°C

Warranty: 24 months

Width (English): 42.52in

Width (English) Interior: 33.07in

Width (English) Shelf: 22.6in

Width (Metric): 1080mm

Width (Metric) Interior: 840mm

Width (Metric) Shelf: 795mm

Height (English): 72.24in

Height (English) Interior: 57.09in

Height (Metric): 1835mm

Height (Metric) Interior: 1450mm

Depth (English): 34.84in

Depth (English) Interior: 24.8in

Depth (Metric): 885mm

Depth (Metric) Interior: 630mm

Shipping Weight (English): 820lbs

Shipping Weight (Metric): 372kg

Electrical Requirements: 100 - 240V, 50-60Hz, 1400W

Voltage: 100/115/220/230 V

Wattage: 900 W

Unit Size: Each