## thermo scientific



# Thermo Scientific Revco RDE Series Ultra-Low Temperature Freezers

Medical Device



# Thermo Scientific™ Revco™ RDE Series Ultra-Low Temperature Freezers

- H-drive hydrocarbon refrigeration system provides sustainable performance with reliability you can count on
- Low peak variation helps ensure sample temperature protection throughout entire cabinet
- Fast door opening recovery in as little as 11 minutes
- Long warm-up time from -80°C to -50°C in up to 5 hours
- Four capacities: 300, 400, 500 and 600 2-inch boxes
- Decrease storage footprint up to 25%
- 5-year standard warranty



## Designed to keep your samples safe

- Worry-free storage; with low peak variation, samples are protected throughout the entire cabinet.¹
- Secure freezer settings with sample security
- FDA Class II Medical Device for Storage of Blood, Plasma, Tissue, Skin, and Bone<sup>3</sup>
- Backed by our Global Service and Support Team

# Limit environmental impact and lower HVAC costs

- Uses as low as 10.7 kWh/day, depending on size
- Less heat emission lowers HVAC costs
- SNAP compliant, natural hydrocarbon refrigerants
- Environmentally-friendly, waterblown foam insulation is compliant with SNAP
- Manufactured in an award-winning, zero-waste-to-landfill facility

#### **User-friendly and quiet**

- New HIC touch screen user interface
- Quiet enough to reside directly in the laboratory; at just 50 dBA, the sound is comparable to a home refrigerator.<sup>2</sup>

<sup>1.</sup> Typical freezer data based on internal testing with freezer setpoint at -80°C and ambient temperature at 20°C. Performance data varies across freezer size and electrical specifications

All data based on internal data unless otherwise noted. Data on file

<sup>3.</sup> FDA Class II Models are listed under product code KSE, regulation number 864.9700. This unit is not intended for use in classified hazardous locations, nor to be used for the storage of flammable inventory.

Reference: AABB - Technical Manual 17th Ed., page 273,274. STANDARDS FOR TISSUE BANKING 14th Ed., Section E, E3.300, E3.310, Table E3.331.

Note for clarity: The 'Bone' is the Osteoarticular Graft, a weight bearing allograft with intact articular surfaces, consisting of a joint with associated soft tissue and bone. STANDARDS FOR TISSUE BANKING 14th Ed., Section page 8.

Dependable storage with operational

savings and sustainability

## User-friendly HIC interface and cabinet

- Easy to use: plug in and go; no setup required
- H-drive Information Center (HIC) combines easy-to-read temperature with simple capacitive touch buttons
- Advanced security features: alarm settings, setpoint security passcode, and padlockcompatible doors
- Egonomic design: single-hand door operation, eye-level display, and shelf-level placement that do not require floor-level loading of racks
- Five inner doors minimize ambient temperature during sample retrieval

## Specifications & Ordering Information









Get Connected

#### Upright Freezers (-50°C to -86°C)

FDA Class II	Сар	acity		Amps / Breaker	Max Shelf	Interior Dimensions	Exterior Dimensions	Shipping
Model	cu. ft. (L)	Cryoboxes (2 in.)	Electrical	(Plug type)	Weight Ibs. (kg)	H x W x D in. (cm)	H x W* x D in. (cm)	Weight lbs. (kg)
RDE30086LA	14.9	300	115V/60Hz	12.6/20 (NEMA 5-20)	125	51.2 x 17.8 x 28.3	78.0 x 23.0 x 38.5	712
RDE30086LD	(422)	300	208-230V/60Hz	5.6/15 (NEMA 6-15)	(57)	(130.1 x 45.2 x 71.9)	(198.1 x 58.4 x 97.7)	(323)
RDE40086LA	19.4	400	115V/60Hz	13.0/20 (NEMA 5-20)	165	51.2 x 23.1 x 28.3	78.0 x 28.3 x 38.5	687
RDE40086LD	(549)	400	208-230V/60Hz	5.9/15 (NEMA 6-15)	(75)	(130.1 x 58.8 x 71.9)	(198.1 x 71.9 x 97.7)	(312)
RDE50086LA	24.1	500	115V/60Hz	12.5/20 (NEMA 5-20)	205	51.2 x 28.8 x 28.3	78.0 x 34.0 x 38.5**	734
RDE50086LD	(682)	500	208-230V/60Hz	5.0/15 (NEMA 6-15)	(93)	(130.1 x 73.0 x 71.9)	(198.1 x 86.4 x 97.7)	(333)
RDE60086LA	28.8	600	115V/60Hz	12.7/20 (NEMA 5-20)	245	51.2 x 34.4 x 28.3	78.0 x 39.6 x 38.5**	820
RDE60086LD	(816)	000	208-230V/60Hz	6.2/15 (NEMA 6-15)	(111)	(130.1 x 87.3 x 71.9)	(198.1 x 100.6 x 97.7)	(372)

<sup>\*</sup>Allowance for handle and hinge, add 4.2 in (10.7 cm) to cabinet width

<sup>\*\*</sup>Doorway width clearance is 34.5 in (87.6 cm) for RDE50086 and RDE60086



## **Performance Data**

Model Series	Energy Consumption* (kW-hr/day)	Peak Variation from -80°C Setpoint (°C)**	60 Second Door Opening Recovery Time (minutes)	Warm-Up Time (-80°C to -50°C) (minutes)***	Noise Level (dBA)
RDE30086	10.7	+6.9/-3.4	11	248	52
RDE40086	12.5	+5.2/-3.7	16	257	51
RDE50086	12.9	+4.0/-2.9	20	260	50
RDE60086	13.8	+3.9/-3.1	24	297	50

<sup>\*</sup>Energy Consumption: Typical data - internal testing with freezer setpoint at -80°C and 20°C ambient temperature

<sup>\*\*</sup>Peak Variation from Setpoint: Typical data - internal testing with freezer setpoint at -80°C and 20°C ambient temperature

<sup>\*\*\*\*</sup>Warm Up Time: Typical data - internal testing with empty freezer setpoint at -80°C and ambient temperature at 20°C

## Options (Field installations must be performed by a qualified professional)

		For Model Series					
Description	Installation	RDE30086	RDE40086	RDE50086	RDE60086		
LN <sub>2</sub> Backup System	Factory	N/A	LN4567	LN4567	LN4567		
Maintains temperature down to -80°C with liquid nitrogen. Models for RDE30086 are stand alone.	Field	FLN300A* FLN300D**	FLN456LEA* FLN456LED**	FLN456LEA* FLN456LED**	FLN456LEA* FLN456LED**		
CO <sub>2</sub> Backup System	Factory	N/A	CO4567	CO4567	CO4567		
Maintains temperature down to -67°C with $\rm CO_2$ . Models for RDE30086 are stand alone.	Field	FCO300A* FCO300D**	FCO456LEA* FCO456LED**	FCO456LEA* FCO456LED**	FCO456LEA* FCO456LED**		
Chart Recorder (Inkless) Seven-day inkless recorder	Factory	N/A	N/A	CR4567	CR4567		
Range: -115° to +50°C (+5°C resolution) Dia.: 6 in. (15.2cm)	Field	N/A	N/A	FCR500LE	FCR600LE		
Chart Recorder (Ink) Seven-day ink recorder	Factory	N/A	N/A	CRP4567	CRP4567		
Range: -100° to +38°C (+2°C resolution) Dia.: 6 in. (15.2cm) Models for RDE30086 and RDE40086 are stand alone.	Field	6383-6A* 6383-6D**	6383-6A* 6383-6D**	FCRP500LE	FCRP600LE		
Stainless Steel Freezer Interior	Factory	SS34567	SS34567	SS34567	SS34567		
Water-Cooled Condenser Option	Factory	N/A	N/A	N/A	WC34567***		
Twist Look Blue NEMA LE 200 for 115V/00Lls	Factory	US125V20ATL	US125V20ATL	US125V20ATL	US125V20ATL		
Twist Lock Plug NEMA L5-20P for 115V/60Hz	Field	TL125V20A	TL125V20A	TL125V20A	TL125V20A		
Twist Lock Plug NEMA L6-15P for 208-230V/60Hz	Factory	US230V15ATL	US230V15ATL	US230V15ATL	US230V15ATL		
I WIST LOCK FILE NEIVIA LO-13P TOT 200-230V/00HZ	Field	TL230V15A	TL230V15A	TL230V15A	TL230V15A		
Turist Local Bloom NEMA LC 00D for 000 000V/COLL	Factory	US230V20ATL	US230V20ATL	US230V20ATL	US230V20ATL		
Twist Lock Plug NEMA L6-20P for 208-230V/60Hz	Field	TL230V20A	TL230V20A	TL230V20A	TL230V20A		

## Accessories

		For Mod	el Series	
Description	RDE30086	RDE40086	RDE50086	RDE60086
Air Filter (Replacement)	AF34567LE	AF34567LE	AF34567LE	AF34567LE
Alarm Delay Module  Eliminates nuisance alarms due to intermittent or transitory conditions. (The alarm conditions must exist for a user-defined period before the signal is broadcast.)	6903	6903	6903	6903
Battery Backup (Replacement)	400159	400159	400159	400159
Chart Paper, for Inkless Recorder, 50/Pack	N/A	N/A	6185	6185
Chart Paper, for Ink Recorder, 50/Pack	17020	17020	17020	17020
Cryo Gloves, Medium	4425	4425	4425	4425
Cryo Gloves, Large	4426	4426	4426	4426
Seismic Restraint Kits	TF-ULT300	TF-ULT400	TF-ULT500	TF-ULT600
Shelf Kits: Include One Shelf and Clips	SK300	SK400	SK500	SK600

<sup>\*</sup>A = 115V/60Hz (NEMA 5-20 plug) \*\*D = 208-230V/60Hz (NEMA 6-15 plug) \*\*\* WC34567 available on 208-230V/60Hz model only

## Freezer Packages with Factory-Installed Options

## Revco RDE Ultra-Low Freezer with Two Shelves of Sliding Drawer Racks Plus Boxes

	Capacity		Electrical.	# of	
Model	cu. ft. (L)	Cryoboxes*	60Hz Racks		Cryoboxes* Included
RDE30086LARK	14.9 (422)	300	115V	6	120
RDE30086LDRK	14.9 (422)	300	208-230V	6	120
RDE40086LARK	19.4 (549)	400	115V	8	160
RDE40086LDRK	19.4 (549)	400	208-230V	8	160
RDE50086LARK	24.1 (682)	500	115V	10	200
RDE50086LDRK	24.1 (682)	500	208-230V	10	200
RDE60086LARK	28.8 (816)	600	115V	12	240
RDE60086LDRK	28.8 (816)	600	208-230V	12	240

<sup>\*</sup>For cryoboxes that measure 5  $\times$  5  $\times$  2 in (12.7  $\times$  12.7  $\times$  5 cm) (W  $\times$  D  $\times$  H)

## Revco RDE Ultra-Low Freezer with LN<sub>2</sub> Backup System, Two Shelves of Sliding Drawer Racks Plus Boxes

Market State	Capacity		Electrical.	# of	0
Model	cu. ft. (L)	Cryoboxes*	60Hz	Racks Included	Cryoboxes* Included
RDE40086LARLN	19.4 (549)	400	115V	8	160
RDE40086LDRLN	19.4 (549)	400	208-230V	8	160
RDE50086LARLN	24.1 (682)	500	115V	10	200
RDE50086LDRLN	24.1 (682)	500	208-230V	10	200
RDE60086LARLN	28.8 (816)	600	115V	12	240
RDE60086LDRLN	28.8 (816)	600	208-230V	12	240

<sup>\*</sup>For cryoboxes that measure 5 x 5 x 2 in (12.7 x 12.7 x 5 cm) (W x D x H)

## Revco RDE Ultra-Low Freezer with CO<sub>2</sub> Backup System, Two Shelves of Sliding Drawer Racks Plus Boxes

M. J.J	Capacity		Electrical.	# of Racks	Cryoboxes* Included
Model	cu. ft. (L)	Cryoboxes*	60Hz	60Hz Included	
RDE40086LARCO	19.4 (549)	400	115V	8	160
RDE40086LDRCO	19.4 (549)	400	208-230V	8	160
RDE50086LARCO	24.1 (682)	500	115V	10	200
RDE50086LDRCO	24.1 (682)	500	208-230V	10	200
RDE60086LARCO	28.8 (816)	600	115V	12	240
RDE60086LDRCO	28.8 (816)	600	208-230V	12	240

<sup>\*</sup>For cryoboxes that measure 5 x 5 x 2 in (12.7 x 12.7 x 5 cm) (W x D x H)



## Freezer Packages with Factory-Installed Options

## Revco RDE Ultra-Low Freezer with Chart Recorder, Two Shelves of Sliding Drawer Racks Plus Boxes

	Cap	Capacity		# of	
Model	cu. ft. (L)	Cryoboxes*	60Hz	Racks Included	Cryoboxes* Included
RDE50086LARCR	24.1 (682)	500	115V	10	200
RDE50086LDRCR	24.1 (682)	500	208-230V	10	200
RDE60086LARCR	28.8 (816)	600	115V	12	240
RDE60086LDRCR	28.8 (816)	600	208-230V	12	240

<sup>\*</sup>For cryoboxes that measure 5 x 5 x 2 in. (W x D x H)  $\,$ 

## Racks for Boxes and Microplates

## Racks for 2 in. (5 cm) Boxes

Catalog No.	Description	Dimensions H x W x D in. (cm)	0	For Model Series			
			Storage Capacities	RDE30086	RDE40086	RDE50086	RDE60086
398329		9.5 x 5.5 x 26.9 (24 x 14 x 68.3)	Boxes/Rack	20	20	20	20
	Sliding Drawer Rack		Racks/Shelf	3	4	5	6
398329			Racks/Freezer	15	20	25	30
			Boxes/Freezer	300	400	500	600
			Boxes/Rack	20	20	20	20
1050510	Adjustable Side	9.4 x 5.4 x 26.75	Racks/Shelf	3	4	5	6
1950518	Access Rack	(23.9 x 13.7 x 67.9)	Racks/Freezer	15	20	25	30
The state of the s			Boxes/Freezer	300	400	500	600

## Racks for 3 in. (7.62 cm) Boxes

Catalog No.	Bernsteller	Dimensions H x W x D in. (cm)	a. a	For Model Series			
Catalog No.	Description		Storage Capacities	RDE30086	RDE40086	RDE50086	RDE60086
398328		9.5 x 5.5 x 26.9 (24 x 14 x 68.3)	Boxes/Rack	15	15	15	15
	Sliding Drawer Rack		Racks/Shelf	3	4	5	6
398328			Racks/Freezer	15	20	25	30
			Boxes/Freezer	225	300	375	450
			Boxes/Rack	15	15	15	15
1050510	Adjustable Side	9.4 x 5.4 x 26.75	Racks/Shelf	3	4	5	6
1950519	Access Rack for 3 in. boxes	(23.9 x 13.7 x 67.9)	Racks/Freezer	15	20	25	30
Ass.			Boxes/Freezer	225	300	375	450

## **Racking Shelf Kits**

	Storage Capacities	For Model Series					
Description	Otorage Capacities	RDE30086	RDE40086	RDE50086	RDE60086		
	Catalog No.	RSK300SD5	RSK400SD5	RSK500SD5	RSK600SD5		
Sliding Drawer Racks with Boxes for One Shelf (5 x 5 x 2 in. Boxes with	Racks Included	3	4	5	6		
100-Count Cell Dividers)	Boxes Included	60	80	100	120		

## **Racks for Standard or Deepwell Microplates**

Catalog No.	Description	Dimensions	Plates/Rack   98   98   98   98   98   98   98   9		For Mode	el Series	Series			
Catalog No.	Description	H x W x D in. (cm)		RDE60086						
			Plates/Rack	98	98	98	98			
200222	Side Access	9.4 x 5.5 x 25.7	Racks/Shelf	3	4	5	6			
398322	398322 Rack with Locking Rod	(23.9 x 14 x 65.3)	Racks/Freezer	15	20	25	30			
			Plates/Freezer	1470	1960	2450	2940			
			Plates/Rack	77	77	77	77			
4050500	Side Access	9.4 x 5.5 x 25.5	Racks/Shelf	3	4	5	6			
1950522	Microplate Rack	(23.9 x 14 x 64.8)	Racks/Freezer	15	20	25	30			
			Plates/Freezer	1155	1540	5 25 2450 2 77 5 25 1925 2	2310			
			Plates/Rack	28	28	28	28			
100000000000000000000000000000000000000	Sliding Drawer	9.4 x 5.5 x 25.7	Racks/Shelf	3	4	5	6			
1950639	Microplate Rack	(23.9 x 14 x 65.3)	Racks/Freezer	15	20	25	30			
			Plates/Freezer	420	560	700	840			

## **Boxes and Dividers**

Catalog No.	Description	# of Dividers	Quantity	Color
5026-0909	Thermo Scientific™ Nalgene™ polycarbonate 2 in. (5.08cm) box for 1.2 to 2mL vials	81	24/Case	White
5954	2 in. (5.08 cm) Fiberboard Box	0	12/Pack	White
820002	2 in. (5.08 cm) Fiberboard Box	81	1	White
820109	2 in. (5.08 cm) Fiberboard Box	100	1	White
5956	3 in. (7.62 cm) Fiberboard Box	0	12/Pack	White
820003	3 in. (7.62 cm) Fiberboard Box	81	1	White
1950878	2 in. (5.08 cm) Fiberboard Box	0	12/Pack	Multiple
1950879	2 in. (5.08 cm) Fiberboard Box	0	12/Pack	Pink
1950880	2 in. (5.08 cm) Fiberboard Box	0	12/Pack	Red
1950881	2 in. (5.08 cm) Fiberboard Box	0	12/Pack	Yellow
1950882	2 in. (5.08 cm) Fiberboard Box	0	12/Pack	Green
1950883	2 in. (5.08 cm) Fiberboard Box	0	12/Pack	Blue
1950884	2 in. (5.08 cm) Fiberboard Box	0	12/Pack	Black

## **Fiberboard Dividers**

Catalog No.	Description	Quantity/Pack
5958	Grid Dividers, Hold 100 x 12 mm Tubes/Vials	12
6212	Grid Dividers, Hold 81 x 13 mm Tubes/Vials	12
5960	Grid Dividers, Hold 64 x 14 mm Tubes/Vials	12
5959	Grid Dividers, Hold 49 x 16 mm Tubes/Vials	12

## **Vials and Tubes**

Catalog No.	Description	Quantity
377267	Thermo Scientific™ Nunc™ 1.8mL Screw-Top Round-Bottom Vials with Internal Threading	1,800/Case

# **Sliding Drawer Racks for Matrix and Cryobank Tubes**Racks work with all Thermo Scientific<sup>™</sup> Matrix<sup>™</sup> and Nunc<sup>™</sup> Cryobank Tubes

		For Model Series	RDE30086	RDE40086	RDE50086	RDE60086
200 μL Ca	pacity Tubes					
		Rack Model No.	1950786	1950786	1950786	1950786
	Matrix 200 μL 2D Internally Threaded Universal Tubes	Freezer Rack Dimensions W x H x D	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)
3747, 3748.		Tubes/Box	96	96	96	96
4988	Box Dimensions: 3.365 x 5.03 x 1.082 in.	Boxes/Rack	42	42	42	42
	(8.5 x 12.8 x 2.75 cm)	Racks/Shelf	3	4	5	6
		Racks/Freezer	15	20	25	30
		Tubes/Freezer	60,480	80,640	100,800	120,960
500 μL Ca	pacity Tubes					
	Matrix 500 µL 2D	Rack Model No.	1950786	1950786	1950786	1950786
3734, 3735, 4898	Open Top Tubes  Box Dimensions: 3.365 x 5.03 x 1.022 in. (8.5 x 12.8 x 2.6 cm)	Freezer Rack Dimensions W x H x D	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)
3736, 3737, 4899	Matrix 200 µL 2D Internally Threaded Universal Tubes with Installed DuraSeal™ Seal	Tubes/Box	96	96	96	96
	Box Dimensions: 3.365 x 5.03 x 1.082 in. (8.5 x 12.8 x 2.75 cm)	Boxes/Rack	42	42	42	42
374086.	Nunc Cryobank 500 µL Internally Threaded Tubes Box Dimensions: 3.365 x 5.03 x 1.394 in. (8.5 x 12.8 x 3.5 cm)	Racks/Shelf	3	4	5	6
374087 (including		Racks/Freezer	15	20	25	30
color options)		Tubes/Freezer	60,480	80,640	100,800	120,960
		Rack Model No.	1950639	1950639	1950639	1950639
3743, 3744, 3745 (including color	Matrix 500 µL 2D Internally Threaded ScrewTop Tubes Box Dimensions: 3.365 x 5.03 x 1.745 in. (8.5 x 12.8 x 4.4 cm)	Freezer Rack Dimensions W x H x D	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)
		Tubes/Box	96	96	96	96
		Boxes/Rack	28	28	28	28
options)		Racks/Shelf	3	4	5	6
		Racks/Freezer	15	20	25	30
		Tubes/Freezer	40,320	53,760	67,200	80,640

# Sliding Drawer Racks for Matrix and Cryobank Tubes Racks work with all Thermo Scientific™ Matrix™ and Nunc™ Cryobank Tubes

		For Model Series	RDE30086	RDE40086	RDE50086	RDE60086
750 μL Cap	pacity Tubes					
	Matrix 750 µL 2D 3731, Open Top Tubes 3732, Box Dimensions: 4896 3.365 x 5.03 x 1.55 in. (8.5 x 12.8 x 3.9 cm)	Rack Model No.	1950639	1950639	1950639	1950639
3732,		Freezer Rack Dimensions W x H x D	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)
		Tubes/Box	96	96	96	96
	Matrix 750 µL 2D Tubes with Installed	Boxes/Rack	28	28	28	28
3729, 4896	DuraSeal Seal Box Dimensions:	Racks/Shelf	3	4	5	6
	3.365 x 5.03 x 1.55 in. (8.5 x 12.8 x 3.9 cm)	Racks/Freezer	15	20	25	30
	(2.2.1.12.1.2.1.2.1.4)	Tubes/Freezer	40,320	53,760	67,200	80,640
1 mL Capa	acity Tubes					
		Rack Model No.	1950639	1950639	1950639	1950639
374088,	Nunc Cryobank 1 mL Internally	Freezer Rack Dimensions W x H x D	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)
374089 (including	Threaded Tubes	Tubes/Box	96	96	96	96
color	Box Dimensions: 3.365 x 5.03 x 1.92 in.	Boxes/Rack	28	28	28	28
options)	(8.5 x 12.8 x 4.9 cm)	Racks/Shelf	3	4	5	6
		Racks/Freezer	15	20	25	30
		Tubes/Freezer	40,320	53,760	67,200	80,640
		Rack Model No.	1950798	1950798	1950798	1950798
3740, 3741, 3742	Matrix 1 mL 2D Internally Threaded Screw Top Tubes Box Dimensions: 3.365 x 5.03 x 2.3 in. (8.5 x 12.8 x 5.8 cm)	Freezer Rack Dimensions W x H x D	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)
		Tubes/Box	96	96	96	96
(including color		Boxes/Rack	21	21	21	21
options)		Racks/Shelf	3	4	5	6
		Racks/Freezer	15	20	25	30
		Tubes/Freezer	30,240	40,320	50,400	60,480

# thermo scientific

## **Sliding Drawer Racks for Matrix and Cryobank Tubes**

Racks work with all Thermo Scientific™ Matrix™ and Nunc™ Cryobank Tubes

		For Model Series	RDE30086	RDE40086	RDE50086	RDE60086
1.4 mL Ca	pacity Tubes					
	Matrix 1.4 mL 2D	Rack Model No.	1950639	1950639	1950639	1950639
3791, 3792, 4890	Open Top Tubes Box Dimensions: 3.365 x 5.03 x 1.92 in. (8.5 x 12.8 x 4.9 cm)	Freezer Rack Dimensions W x H x D	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)
3801,	1.4 mL 2D Tubes with Installed DuraSeal Seal	Tubes/Box	96	96	96	96
4890	Box Dimensions: 3.365 x 5.03 x 1.92 in. (8.5 x 12.8 x 4.9 cm)	Boxes/Rack	28	28	28	28
	Matrix 1.4 mL Human Readable	Racks/Shelf	3	4	5	6
3711, 3112, 4890	Open Top Tubes Box Dimensions:	Racks/Freezer	15	20	25	30
	3.365 x 5.03 x 1.92 in. (8.5 x 12.8 x 4.9 cm)	Tubes/Freezer	40,320	53,760	67,200	80,640
1.8 to 2 ml	L Capacity Tubes					
	Nunc 1.8 mL	Rack Model No.	1950639	1950639	1950639	1950639
374500, 374501	Externally Threaded Universal Tubes Box Dimensions: 3.365 x 5.03 x 2.15 in. (8.5 x 12.8 x 5.5 cm)	Freezer Rack Dimensions W x H x D	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)
	Nunc Cryobank 2 mL Internally Threaded Tubes Box Dimension: 3.365 x 5.03 x 2.15 in. (8.5 x 12.8 x 5.5 cm)	Tubes/Box	48	48	48	48
		Boxes/Rack	28	28	28	28
374221, 374223		Racks/Shelf	3	4	5	6
07 1220		Racks/Freezer	15	20	25	30
		Tubes/Freezer	20,160	26,880	33,600	40,320
5 mL Cap	acity Tubes					
		Rack Model No.	1950818	1950818	1950818	1950818
	Nunc Cryobank 5 mL Internally Threaded Tubes Box Dimensions: 3.365 x 5.03 x 3.78 in. (8.5 x 12.8 x 9.6 cm)	Freezer Rack Dimensions W x H x D	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)	5.5 x 9.5 x 26.96 in. (14 x 24 x 68.5 cm)
374220,		Tubes/Box	48	48	48	48
374222		Boxes/Rack	14	14	14	14
		Racks/Shelf	3	4	5	6
		Racks/Freezer	15	20	25	30

