Titan Portable PA-800







Titan AC/Battery powered portable sound system (basic unit). The Input Panel provides a Lo-z XLR Microphone Input with Volume Control, Stereo Line Input with volume control and Dual Line Output, Treble & Bass Controls, Master Volume Control. Voice Priority Circuit and Battery Level Indicator.

Specifications

Output Power 50 W RMS, 80 W Max Sensitivity 91dB, 1W @ 1M

Maximum SPL 95 dB

Frequency Response 20 Hz - 20 kHz (audio) 8" LF Neodymium Woofer Speaker

1" HF Horn

>70dB Signal to noise Ratio

XLR-TRS Balanced Mic Audio Input

> Line Level, Dual RCA Line Level, Dual RCA

Audio Output Controls Master Volume, Treble, Bass

Mic Vol.

Rechargeable Battery Type Two 12 VDC / 4.1 AH, NiMH

Operating Life About 6-8 hours Charging Time About 8-10 hours **Power Supply** 100-240 V AC Input

European Approval 11 ¾" W x 18 ½" H x 9" D **Dimensions**

21 lbs. Weight

Features

- New Auto Scan UHF Wireless Module
- New Neodymium LF Speaker
- New Nickel Metal Hydride batteries
- New Four stage battery level indicator
- Light Weight
- Durable high impact enclosure
- Efficient two-way speaker system
- Simultaneous mixing with the microphone inputs
- Plug-In microphone Lo-z, XLR Connection
- Treble and bass controls
- Dual line input and output (RCA)
- Rechargeable Nickel Metal Hydride batteries for an extended 6-8 hours of continuous use
- AC Operable without batteries being fully charged
- AirLink transmitter for wireless transmission of program to powered companion speaker
- Voice Priority Switch
- Can be upgraded to include up to two Wireless Auto Scan
- Receiver, Wireless Transmitter & CD/MP3 Player
- AirLink Router and Spartan compatible



