

CONCRETE INSPECTION EZ KIT



Product code: CZK5.2

A compact kit designed for the instant and precise measurement of moisture content in concrete slabs and giving comparative readings in other cementitious floor screeds. Allowing for testing per international standards BS 8201, 8203, 5325 and ASTM F2659, F2170 (and ASTM F2420 with optional Hood), the Concrete Inspection EZ Kit comes in a protective Tramex Easy-travel case.

CONTENTS

1. CMEX II - concrete meter.
2. 3 x Hygro-i ® probes.
3. 12 x Hole Liners.

FEATURES OF CMEX II

- Measures up to 6.9% Moisture Content in Concrete.
- CM Carbide Method moisture content equivalent readings.
- Large clear backlit digital display.
- Hold function "freezes" meter reading when inspecting areas where the meter face is not visible.
- Attaches to a relative humidity Hygro-i ® probe for in situ testing of concrete.
- 7% to 40% Moisture Content measurement in Wood using Pin-type probe attachment. (optional)



MEASURING RANGE

Depth of penetration: (NDT*)	approx. 20 mm (¾")
Moisture content for Concrete: (NDT*)	0 to 6.9 %
Carbide Method Equivalent for concrete: (NDT*)	0 to 4.3
Reference scale: (NDT*)	0 to 100
Relative Humidity (with Hygro-i ® probe):	0 to 99%
Humidity accuracy:	10% to 90%RH +/-1.8% @ 25°C / 77°F

*NDT - Non-destructive Test

SPECIFICATIONS OF KIT

Size:	350mm x 230mm x 90mm (13.8" x 9.1" x 3.5")
Weight:	1.55kg (3.4lbs)
Power:	2 x 9 volt PP3 Batteries (included)



CZK5.2-EU 06/14 REV.1.1



Non-destructive



Ambient



In situ