

Technical Information

Page 1 of 2



Part No.: 7110.B530.SET.WT

◆ Untere Gießwiesen 21 ◆ 78247 Hilzingen ◆ Tel.: +49-7731-86880 ◆ Fax: +49-7731-868830

Wolfgang Warmbier®
Systeme gegen Elektrostatisik

ESD-AUDIT-KIT B530 (Special Version)

Part No.: 7110.B530.SET.WT

The ESD-Audit-Kit includes instruments and equipment needed to perform ESD auditing according to IEC 61340-5-1 and verification of ESD control elements.

Applications:

- Testing flooring systems acc. to IEC 61340-4-1 and to IEC 61340-4-5
- Testing chairs, workstations, shelves, transport cars and automated handling equipment acc. IEC 61340-2-3
- Testing packaging materials acc. to IEC 61340-2-3
- Testing the point-to-point resistance of garments acc. to IEC 61340-4-9
- Testing electrostatic fields
- Evaluating Ionizers acc. to IEC 61340-4-7
- Performing a Walking Test to verify the personnel charging within an EPA



Technical data:

Outer dimensions	575 x 490 x 250 mm
Weight	20 kg

Contents:



7100.B530.G *

High resistance meter B530 with connecting cables



7100.SRM110 .A*

Surface Resistance Meter SRM®110



7220.840 *

Two-Point-Probe model 840



7100.EFM51.CPS *

Electrostatic Field Meter EFM®51 with charged plate set



7220.880 *

Ring probe model 880



7220.870

Probe model 870
(2 probes)



7220.880.9

Metal counter-electrode
Ø 120 mm



7220.870.V.SET

Set extension and T-heat



7220.880.6

2 Insulation plates
120 x 120 x 6 mm



7110.E8

8-socket grounding box

We believe all the information in these pages including technical data to be reliable. However we make no warranties expressed or implied and assume no liability regarding any use of this information.

Technical Information

Page 2 of 2

Part No.: 7110.B530.SET.WT



Certified by DQS
ISO 9001:2008



◆ Untere Gießwiesen 21 ◆ 78247 Hilzingen ◆ Tel.: +49-7731-86880 ◆ Fax: +49-7731-868830



7100.2000.TR50

Cable reel, 50 m



2200.110

Grounding plug



7220.45

Handheld probe model 45
Ø 25 x 75 mm



7100.PGT100.102

Metal plate 400 x 300 x 2 mm



7100.TF530 *

Temperature and humidity sensor

7100.EFM51.WT.MK

Voltage head up to 4KV



2287.10.10

Banana plug adapter 10mm



7100.WT5000.ML

Connecting cable 3m

* These instruments are supplied with a calibration certificate

- Recommended calibration interval: 2 years
- 1 year limited warranty on all instruments