

|                           |                                      |
|---------------------------|--------------------------------------|
| <b>Weight</b>             | <b>12 lbs</b>                        |
| <b>Dimensions</b>         | <b>26 × 10 × 7 in</b>                |
| <b>Coverage</b>           | <b>2ft. x 3ft. area</b>              |
| <b>Decay</b>              | <b>Less Than 3secs at 18in.</b>      |
| <b>Balance</b>            | <b>0 +10 volts</b>                   |
| <b>Power Input</b>        | <b>120V AC</b>                       |
| <b>Approvals</b>          | <b>CE</b>                            |
| <b>Air Volume</b>         | <b>100 CFM – 200 CFM [low –high]</b> |
| <b>Audible Noise</b>      | <b>48dB(A), (Distance 1 meter)</b>   |
| <b>Enclosure</b>          | <b>Steel</b>                         |
| <b>Finsh</b>              | <b>Powder coat, gray</b>             |
| <b>Ozone Production</b>   | <b>&lt; 0.003 ppm, 12" in</b>        |
| <b>RH Operating Range</b> | <b>20-60%, non-condensing</b>        |
| <b>Warranty</b>           | <b>1 Year (Manufacturer Defects)</b> |
| <b>Temperature</b>        | <b>32-122° F (0-50° C)</b>           |