

8150-BR-KIT CamView IP Pro 5 HD CCTV Camera Tester with Borescope

Adds a borescope function to your security camera tester for inspecting behind walls and hard-to-reach areas

8150 Features:

- 8MP tester (1080p) with HDMI, BNC, and RJ45 ports
- Works with IP cameras, analog cameras, TVI, CVI, AHD cameras, as well as for testing 4K H.264 /H.265
- WiFi for connecting to WiFi cameras and to create a WiFi hotspot
- Has PoE (24W) and DC power output (12V/3A)
- Auto-recognize HD coax camera type and resolution
- RJ45 TDR cable test and cable quality test
- UTP cable test detects opens, shorts and miswires
- 4 hour run time with 2-3-hour charge
- Compact and lightweight
- Includes SBR2M Security Camera Borescope accessory, 7.4V Li-ion battery, AC adapter/charger, DC power cable, BNC cable, RS485 cable, audio cable, wrist strap and carrying case

SBR2M Borescope Features:

- Waterproof (IP67) 8mm camera (Lens only)
- 8mm lens diameter with 2m cable (6.5ft)
- 6 adjustable LEDs with thumbwheel control
- Power provided by the camera tester (12V 1/2/3A) — no batteries needed
- Utilizes the display resolution of your camera tester
- Image snapshot and Video record functions
- Compatible with most camera testers

Applications:

Designed for the maintenance and installation of IP cameras, analog cameras, TVI, CVI, AHD cameras, as well as for testing 4K H.264 /H.265. The 1920 x 1200 resolution enables it to display network HD cameras and analog cameras in high resolution.

Borescope for inspecting behind walls and hard-to-reach areas; checking cable connections on the back of installed equipment; Insect or rodent infestation; Anywhere you need to see underneath and behind difficult to move objects

Ordering Information:

8150-BR-KIT CamView IP Pro 5 HD CCTV Camera Tester with Borescope
SBR2M Security Camera Tester Borescope, 2M



Specifications

| | 8150 |
|-------------------------|--|
| 8MP AHD | √ |
| 8MP TVI | √ |
| 8MP CVI | √ |
| 4k IP / Analog | √ |
| Wifi | Connect to WiFi cameras & create a WiFi hotspot |
| HDMI Output (1080p) | √ |
| DC 12V 3A Power Output | √ |
| 48V PoE Output | √ |
| Advanced UTP cable test | √ |
| Power | Rechargeable 7.4V 3350mAh Li-ion battery |
| Dimensions | 7.2 x 4.3 x 1.4" (183 x 110 x 36.5mm) |
| Weight | 11.3oz (320g) |
| | SBR2M |
| Camera | 8mm |
| Field of View | 60° |
| Depth of View | 1.2 to 4" (3 to 10cm) |
| Cable Length | 2m (6.5ft) |
| Resolution | 640 x 480 |
| Illumination | 6 adjustable LEDs |
| Still Image Capture | dependent on camera tester |
| Video Recording | dependent on camera tester |
| Power | 12V 1/2/3A (provided by camera tester) |
| Interface | BNC |
| Dimensions | Camera & Cable: 6.5ft x 0.3" (2m x 8mm) LED Thumbwheel: 2x0.5x0.25" (51x13x6.4mm) |
| Weight | 5.6oz (159g) |