

# 1U Rack-Mount Power Strip, 120V, 15A, 5-15P, 12 Right-Angle 5-15R Outlets (6 Front-Facing, 6 Rear-Facing), 15 ft. (4.57 m) Cord

MODEL NUMBER: RS-1215-RA



Delivers 120V power to rack-mount equipment in your network closet or server room.

## Features

### 12-Outlet Power Strip for Your Rack Equipment

This 120V power strip is a versatile all-metal cabinet with 12 NEMA 5-15R outlets — six in front and six in back. The outlets are widely spaced to accommodate bulky transformers without blocking any outlets. Unfiltered electrical pass-through makes the RS-1215-RA ideal for distributing alternate waveform UPS or generator power in your data center or network closet's rack enclosure. The outlets are oriented at a right angle with the ground pin at the bottom.

### Features Safety Standards and Versatile Installation Options

A lighted power switch with snap-in switch guard confirms on/off status at a glance and helps prevent accidental shutdowns. A 15A circuit breaker protects connected equipment. Detachable mounting brackets allow installation on a wall, under a counter or in 1U of space in an EIA-standard 19-inch rack. The 15-foot (4.6-meter) power cord with NEMA 5-15P plug connects to a compatible AC outlet.

## Highlights

- 12 NEMA 5-15R outlets are spaced apart to accommodate bulky transformers
- Lighted on/off switch with plastic cover is protected against accidental turn-off
- 15 ft. cord with NEMA 5-15P plug is long enough to reach distant AC outlet
- Versatile installation on wall, under counter or in 1U of rack space

## Package Includes

- RS-1215-RA 1U Rack-Mount Power Strip
- Owner's manual

## Specifications

| OVERVIEW                           |              |
|------------------------------------|--------------|
| UPC Code                           | 037332099402 |
| INPUT                              |              |
| Nominal Input Voltage(s) Supported | 120V AC      |
| Recommended Electrical Service     | 15A 120V     |
| Voltage Compatibility (VAC)        | 120          |
| Input Plug Type                    | NEMA 5-15P   |
| Input Cord Length (ft.)            | 15           |



Powering Business Worldwide

**TRIPP-LITE**  
by **EATON**

|                                              |                                                                                                                        |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Right-Angle Plug                             | No                                                                                                                     |
| Input Cord Length (m)                        | 4.57                                                                                                                   |
| Integrated Cord Clip                         | No                                                                                                                     |
| <b>OUTPUT</b>                                |                                                                                                                        |
| Frequency Compatibility                      | 50 / 60 Hz                                                                                                             |
| Output Receptacles                           | (12) 5-15R                                                                                                             |
| Circuit Breaker (amps)                       | 15                                                                                                                     |
| Transformer Accommodation                    | (9) Yes                                                                                                                |
| Outlet Orientation                           | 6 front-facing / 6 rear-facing, all with ground pin oriented to the bottom (when viewed in 1U rackmount configuration) |
| Right-Angle Outlets                          | Yes                                                                                                                    |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                                                                                                        |
| Switches                                     | Lighted 2 position switch controls power to all outlets                                                                |
| Locking Switch Cover                         | Transparent locking switch cover prevents accidental shutoff                                                           |
| <b>PHYSICAL</b>                              |                                                                                                                        |
| Color                                        | Black                                                                                                                  |
| Material of Construction                     | Metal                                                                                                                  |
| Power Cord Color                             | Black                                                                                                                  |
| Form Factors Supported                       | 1U rackmount, wall-mount and undercounter installation supported                                                       |
| Housing Color                                | Black                                                                                                                  |
| Included Mounting Accessories                | Rackmount flanges                                                                                                      |
| Mounting Holes or Slots                      | No                                                                                                                     |
| Outlets Measurement (Center to Center)       | Distance between Front outlets = 2.03 in.; Distance between Rear outlets = 2.79 in.                                    |
| Receptacle Color                             | Black                                                                                                                  |
| Shipping Dimensions (hwd / in.)              | 9.30 x 2.25 x 20.30                                                                                                    |
| Shipping Dimensions (hwd / cm)               | 23.62 x 5.72 x 51.56                                                                                                   |
| Shipping Weight (lbs.)                       | 5.32                                                                                                                   |
| Shipping Weight (kg)                         | 2.41                                                                                                                   |
| Unit Dimensions (hwd / in.)                  | 1.750 x 19.000 x 4.000                                                                                                 |
| Unit Dimensions (hwd / cm)                   | 4.445 x 44.45 x 11.4                                                                                                   |
| Unit Weight (lbs.)                           | 4.6                                                                                                                    |
| Unit Weight (kg)                             | 2.09                                                                                                                   |
| <b>ENVIRONMENTAL</b>                         |                                                                                                                        |
| Operating Temperature Range                  | 32° to 113°F (0° to 45°C)                                                                                              |

| FEATURES & SPECIFICATIONS           |                                       |
|-------------------------------------|---------------------------------------|
| Rotatable Outlets                   | No                                    |
| Antimicrobial                       | No                                    |
| Built-In Circuit Breaker            | Yes                                   |
| Grounding                           | Back panel nut and bolt grounding lug |
| STANDARDS & COMPLIANCE              |                                       |
| Product Certifications              | cUL Listed; UL 1363; UL Listed        |
| Product Compliance                  | RoHS                                  |
| WARRANTY & SUPPORT                  |                                       |
| Product Warranty Period (Worldwide) | Lifetime limited warranty             |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.