

## Protect It! 6-Outlet Surge Protector, 6 ft. Cord, 790 Joules, Diagnostic LED, Black Housing

MODEL NUMBER: TLP606B



Safeguard your computer, printer, scanner, router, modem and other small home electronics against dangerous surges, spikes and line noise.

### Description

Perfect for your home or office workstation, the TLP606B Protect It!® 6-Outlet Surge Protector features a surge protection rating of 790 joules to defend your sensitive electronic components against strong surges and spikes.

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP606B protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G). It also filters out electromagnetic interference (EMI) and radio frequency interference (RFI) that can disrupt your electronics and inflict hardware damage or data loss.

Your devices plug into six NEMA 5-15R outlets, one of which is placed at the end to accept a bulky transformer without blocking adjacent outlets. An integrated 15A circuit breaker protects all outlets and shuts down connected equipment in case of overload. The lighted on/off switch provides one-touch control over connected equipment. A diagnostic LED confirms your connected equipment is protected.

The six-foot (1.8-meter) AC power cord with NEMA 5-15P plug reaches nearby outlets to fit easily into your workstation or home theater setup. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black plastic housing.

### Features

**790-Joule Surge Protection for Home or Office Electronics** Protects your computer, printer, scanner, router, modem and other small home electronics against even the strongest surges and spikes  
Recommended for any desktop, network or home electronics application requiring AC line protection  
Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression  
Filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss  
Exceeds IEEE 587 Category A and B surge suppression specifications

**6 Outlets Accept Wide Range of Electronic Devices** 6 NEMA 5-15R AC outlets accept most computers and peripherals  
Special end outlet designed for bulky transformers without blocking other outlets

**Premium Safety Features** Lighted on/off switch provides one-touch control over connected equipment  
Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required  
Diagnostic LED confirms protection status at a glance  
Conforms to current UL 1449 3rd Edition safety standards

**Fits Effortlessly Into Your Workstation** 6 ft. AC power cord with NEMA 5-15P plug reaches nearby outlets  
Keyhole slots on bottom panel provide convenient wall or desk mounting options  
Black plastic housing designed for long life

### Highlights

- 6 NEMA 5-15R outlets—one designed for a bulky transformer
- 790-joule surge protection rating
- Filters out threatening EMI/RFI line noise
- 15A resettable circuit breaker prevents dangerous overloads
- 6 ft. AC power cord with NEMA 5-15P plug

### Package Includes

- TLP606B Protect It! 6-Outlet Surge Protector, Black Housing
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

**Backed by Ultimate Lifetime Insurance**\$20,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

## Specifications

| OVERVIEW                           |                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------|
| UPC Code                           | 037332138293                                                                      |
| INPUT                              |                                                                                   |
| Nominal Input Voltage(s) Supported | 120V AC                                                                           |
| Recommended Electrical Service     | 120V (110-125V)                                                                   |
| Input Cord Gauge Type              | 14 gauge; SJT                                                                     |
| Input Cord Gauge (AWG)             | 14                                                                                |
| Voltage Compatibility (VAC)        | 120                                                                               |
| Maximum Surge Amps                 | 35500                                                                             |
| Input Plug Type                    | NEMA 5-15P                                                                        |
| Input Cord Details                 | SJT                                                                               |
| Input Cord Length (ft.)            | 6                                                                                 |
| Right-Angle Plug                   | No                                                                                |
| Input Cord Length (m)              | 1.83                                                                              |
| Integrated Cord Clip               | No                                                                                |
| OUTPUT                             |                                                                                   |
| Frequency Compatibility            | 50 / 60 Hz                                                                        |
| Output Receptacles                 | (6) 5-15R                                                                         |
| Circuit Breaker (amps)             | 15                                                                                |
| Overload Protection                | 15A resettable illuminated combo switch / circuit breaker                         |
| Transformer Accommodation          | (2) Yes                                                                           |
| Outlet Orientation                 | Single row of 6 outlets                                                           |
| Right-Angle Outlets                | No                                                                                |
| USER INTERFACE, ALERTS & CONTROLS  |                                                                                   |
| Diagnostic LED(s)                  | Yes                                                                               |
| Switches                           | Combination AC circuit breaker and 2 position red illuminated on/off power switch |
| Diagnostic LED Details             | Built-in LED confirms suppressor "protection present" (green) status              |
| SURGE / NOISE SUPPRESSION          |                                                                                   |
| AC Suppression Joule Rating        | 790                                                                               |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                                   |                                                                                                           |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| AC Suppression Response Time                      | < 1 ns                                                                                                    |
| Protection Modes                                  | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression                              |
| UL1449 Let Through Rating                         | 500V                                                                                                      |
| EMI / RFI Filtering                               | Yes                                                                                                       |
| Automatic Shut-Off                                | Yes                                                                                                       |
| <b>DATALINE SURGE SUPPRESSION</b>                 |                                                                                                           |
| Cable (Coax) Protection                           | No                                                                                                        |
| Network (Ethernet) Protection                     | No                                                                                                        |
| Telephone/DSL Protection                          | No                                                                                                        |
| <b>PHYSICAL</b>                                   |                                                                                                           |
| Material of Construction                          | Plastic                                                                                                   |
| Power Cord Color                                  | Black                                                                                                     |
| Housing Color                                     | Black                                                                                                     |
| Mounting Holes or Slots                           | Yes                                                                                                       |
| Slot or Hole Mount Measurement (Center to Center) | Distance between slots = 101 mm; Distance between slot height = 28 mm                                     |
| Outlets Measurement (Center to Center)            | 28.5mm                                                                                                    |
| Receptacle Color                                  | Black                                                                                                     |
| Shipping Dimensions (hwd / in.)                   | 12.50 x 1.60 x 5.00                                                                                       |
| Shipping Dimensions (hwd / cm)                    | 31.75 x 4.06 x 12.70                                                                                      |
| Shipping Weight (lbs.)                            | 1.20                                                                                                      |
| Shipping Weight (kg)                              | 0.54                                                                                                      |
| Unit Dimensions (hwd / in.)                       | 10.800 x 1.850 x 1.230                                                                                    |
| Unit Dimensions (hwd / cm)                        | 27.43 x 4.70 x 3.12                                                                                       |
| Unit Weight (lbs.)                                | 1.01                                                                                                      |
| Unit Weight (kg)                                  | 0.46                                                                                                      |
| <b>FEATURES &amp; SPECIFICATIONS</b>              |                                                                                                           |
| Rotatable Outlets                                 | No                                                                                                        |
| Antimicrobial                                     | No                                                                                                        |
| <b>STANDARDS &amp; COMPLIANCE</b>                 |                                                                                                           |
| Product Certifications                            | CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed |
| Product Compliance                                | RoHS                                                                                                      |
| <b>WARRANTY &amp; SUPPORT</b>                     |                                                                                                           |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                                               |                                                                                                                         |
|---------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Product Warranty Period<br>(Worldwide)                        | Lifetime limited warranty                                                                                               |
| Connected Equipment Insurance<br>(U.S., Canada & Puerto Rico) | \$20,000 <a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.