

UR8450-3D

Specification

Detail

Product Name	UR8450-3D
Planar Part Number	997-7108-00
Screen Size	84 in. (diagonal)
Orientation	Landscape
Recommended Usage	Up to 24/7 mission critical operation
Aspect Ratio	16:9
Brightness (typ)	420 nits
Backlight	LED
Contrast Ratio (typ)	500,000:1 (dynamic)
Response Time (typ)	5 ms
Frame Rate	120Hz
Viewing Angle (typ)	178°
Native Resolution	3840 x 2160
Display Color	>1 billion colors. Full 10 bit data path
Display Active Area	73.2" (1860.5mm) wide x 41.2" (1046.5mm) tall
Surface Treatment	Anti-reflectance/gloss
Control and Monitoring	IR, RS-232, USB, LAN
Line Voltage	100-240V; 50/60Hz
Power Consumption (typ)	460W
External Connections	4 x DisplayPort 1.1a; 4 x HDMI with Deep Color and 4K support; 1 x RS-232; 1 x LAN 10/100BaseT; 1 x USB 2.0; 1 x IR
Operating Temperature	0C to +40C
Storage and Transport Temperature	-20° to +60°C (-4° to 140°F)
Humidity	up to 85% RH (non-condensing)
Display dimensions	75.5" W x 43.7" H x 3.05" D (1918.7mm W x 1110.7mm H x 77.5mm D)
Bezel Width	1.14" (29.1mm) left/right; 1.26" (32.1mm) top/bottom
Dimensions, including wall mount	75.5" W x 43.7" H x 3.17" D (1918.7mm W x 1110.7mm H x 80.5mm D)
Weight	180 lbs. (82 kg)
Weight, including mount	210 lbs (95.25 kg)
Weight (Shipping)	265 lbs. (120 kg)
Approvals	FCC Class A, EN55022/CISPR22, ICES-003, EN55024, CNS 13438, EN60950-1, CE, cTUVus, EU RoHS

Options / Features

Extended Warranty to 5 years

Warranty

3 years Advance Exchange

UPC

8 10689 07108 2

Touch Technology

N/A

OS Compatibility

N/A

The logo for Touchboards features the word "Touchboards" in a bold, black, sans-serif font. The letters "T", "C", and "B" are each enclosed within a square frame of a different color: yellow for "T", blue for "C", and orange for "B". The remaining letters "o", "u", "c", "h", "b", "o", "a", "r", "d", "s" are in plain black text.

205 Westwood Ave, Long Branch, NJ 07740

Phone: 866-94 BOARDS (26273) / (732)-222-1511

Fax: (732)-222-7088 | E-mail: sales@touchboards.com