

UR8450-LX

Specification

Detail

Product Name	UR8450-LX
Planar Part Number	997-7049-00
Screen Size	84 in. (diagonal)
Orientation	Landscape
Recommended Usage	Up to 24/7 mission critical operation
Aspect Ratio	16:9
Brightness (typ)	350 nits
Backlight	LED
Contrast Ratio (typ)	500,000:1 (dynamic)
Response Time (typ)	5 ms
Frame Rate	120Hz
Viewing Angle (typ)	178°
Native Resolution	3840 x 2160
Display Color	>1 billion colors. Full 10 bit data path
Display Active Area	73.2" (1860.5mm) wide x 41.2" (1046.5mm) tall
Surface Treatment	Low-reflectance/matte
Control and Monitoring	IR, RS-232, USB, LAN
Line Voltage	100-240V; 50/60Hz
Power Consumption (typ)	460W
External Connections	4 x DisplayPort 1.1a; 4 x HDMI with Deep Color and 4K support; 1 x RS-232; 1 x LAN 10/100BaseT; 1 x USB 2.0; 1 x IR
Operating Temperature	0° to +40° C
Storage and Transport Temperature	-20° to +60°C (-4° to 140°F)
Humidity	up to 85% RH (non-condensing)
Display dimensions	75.5" W x 43.7" H x 3.05" D (1918.7mm W x 1110.7mm H x 77.5mm D)
Bezel Width	1.14" (29.1mm) left/right; 1.26" (32.1mm) top/bottom
Dimensions, including wall mount	75.5" W x 43.7" H x 3.17" D (1918.7mm W x 1110.7mm H x 80.5mm D)
Weight	180 lbs. (82 kg)
Weight, including mount	210 lbs (95.25 kg)
Weight (Shipping)	265 lbs. (120 kg)
Approvals	FCC Class A, EN55022/CISPR22, ICES-003, EN55024, CNS 13438, EN60950-1, CE, cTUVus, EU RoHS

Options / Features

Extended Warranty to 5 years

Warranty

3 years Advance Exchange

UPC

8 10689 07049 8

Touch Technology

N/A

OS Compatibility

N/A

The logo for Touchboards features the word "Touchboards" in a bold, black, sans-serif font. The letters are set against a background of three overlapping squares: a yellow square on the left, a blue square in the middle, and an orange square on the right. The squares are slightly offset, creating a layered effect behind the text.

205 Westwood Ave, Long Branch, NJ 07740

Phone: 866-94 BOARDS (26273) / (732)-222-1511

Fax: (732)-222-7088 | E-mail: sales@touchboards.com