

## UR8450-LX-ERO-B-T

### Specification

### Detail

Product Name	UR8450-LX-ERO-T
Planar Part Number	997-7131-00
Screen Size	84 in. (diagonal)
Orientation	Landscape
Recommended Usage	Up to 24/7 mission critical operation
Aspect Ratio	16:9
Brightness (typ)	350 nits
Backlight	LED
Contrast Ratio (typ)	500,000:1 (dynamic)
Response Time (typ)	5 ms
Frame Rate	120Hz
Viewing Angle (typ)	178°
Native Resolution	3840 x 2160
Display Color	>1 billion colors. Full 10 bit data path
Display Active Area	73.2" (1860.5mm) wide x 41.2" (1046.5mm) tall
Surface Treatment	Anti-Reflectant ERO(tm) optically bonded glass
Control and Monitoring	IR, RS-232, USB, LAN
Line Voltage	100-240V; 50/60Hz
Power Consumption (typ)	460W
External Connections	4 x DisplayPort 1.1a; 4 x HDMI with Deep Color and 4K support; 1 x RS-232; 1 x LAN 10/100BaseT; 1 x USB 2.0; 1 x IR
Operating Temperature	0° to +40° C
Storage and Transport Temperature	-20° to +60°C (-4° to 140°F)
Humidity	up to 85% RH (non-condensing)
Display dimensions	77.34" x 45.27" (1964.4mm x 1149.9mm)
Bezel Width	1.95" (49.5mm)
Dimensions, including wall mount	77.34" x 45.27" x 3.83" (1964.4mm x 1149.9mm x 97.3mm)
Weight	240 lbs. (109kg)
Weight, including mount	270 lbs (123kg)
Weight (Shipping)	325 lbs (147.4kg)
Approvals	FCC Class A, EN55022/CISPR22, ICES-003, EN55024, CNS 13438, EN60950-1, CE, cTUVus, EU RoHS
Options / Features	Extended Warranty to 5 years

Warranty	3 years Advance Exchange
UPC	N/A
Touch Technology	IR 6 point touch
OS Compatibility	Windows 7, 8, Vista, XP, Mac OSX and Linux



205 Westwood Ave, Long Branch, NJ 07740  
Phone: 866-94 BOARDS (26273) / (732)-222-1511  
Fax: (732)-222-7088 | E-mail: sales@touchboards.com