



DM505



DM515

## Key Selling Points

### Professional Functionality

The DM505 and DM515 digital multimeters offer professionals comprehensive functionality, reliable safety and expected durability. Both feature 1000 volts, 10 amps, resistance, diode test, capacitance, continuity and 1 millisecond response fast min/max. The DM515 adds True RMS accuracy and temperature.

### Real-World Design

These meters are ETL listed to the newer 3rd edition safety standard and rated CATIII 600V/CATII 1000V. Both feature a drop protection design and ingress protection against dirt and water.

## Competitive Comparison

### DMM Comparison

| Brand                  | UEi                         | Fluke                       | UEi                                  | Fluke                            |
|------------------------|-----------------------------|-----------------------------|--------------------------------------|----------------------------------|
| Model #                | DM505                       | 15B+                        | DM515                                | 17B+                             |
|                        |                             |                             |                                      |                                  |
| True RMS               |                             | Avg AC                      | •                                    | Avg AC                           |
| Safety                 | CATIII 600V/<br>CATII 1000V | CATIII 600V/<br>CATII 1000V | CATIII 600V/<br>CATII 1000V          | CATIII 600V/<br>CATII 1000V      |
| AC Volts               | 1V to 1000V                 | 4V to 1000V                 | 1V to 1000V                          | 4V to 1000V                      |
| DC Volts               | 1V to 1000V                 | 4V to 1000V                 | 1V to 1000V                          | 4V to 1000V                      |
| AC Amps                | 1A to 10A                   | 4A to 10A                   | 1A to 10A                            | 4A to 10A                        |
| DC Amps                | 1A to 400mA                 | 4A to 10A                   | 1A to 10A                            | 4A to 10A                        |
| AC/DCmV                | 6mV                         | 400mV                       | 6mV                                  | 400mV                            |
| AC/DC mA               | 400mA                       | 400mA                       | 400mA                                | 400mA                            |
| DCµA                   | 600µA                       | 40000µA                     | 600µA                                | 40000µA                          |
| AC µA                  | 600µA                       | •                           | 600µA                                | •                                |
| Resistance             | 40MΩ                        | 40MΩ                        | 40MΩ                                 | 40MΩ                             |
| Capacitance            | 10nF to 9999µF              | 50nF to 100.0µF             | 10nF to 9999µF                       | 50nF to 100.0µF                  |
| Continuity             | •                           | •                           | •                                    | •                                |
| Diode test             | •                           | •                           | •                                    | •                                |
| Rubber Boot            | •                           | •                           | •                                    | •                                |
| Kick Stand             | •                           | •                           | •                                    | •                                |
| Display Count          | 6,000                       | 4,000                       | 6,000                                | 4,000                            |
| Ranging                | Auto/Manual                 | Auto/Manual                 | Auto/Manual                          | Auto/Manual                      |
| IP                     | 42                          | 40                          | 42                                   | 40                               |
| Magnetic Hanger insert | •                           | •                           | •                                    | •                                |
| Fast Response Min/Max  | •                           |                             | •                                    |                                  |
| Battery Test           | •                           |                             |                                      |                                  |
| Backlit Display        | •                           |                             | •                                    |                                  |
| Temperature            |                             |                             | -328° to 2462°F<br>(-200° to 1350°C) | -67° to 752°F<br>(-55° to 400°C) |
| Frequency              |                             |                             |                                      | •                                |
| Duty Cycle             |                             |                             |                                      | •                                |
| Includes               |                             |                             |                                      |                                  |
| Test Leads             | •                           | •                           | •                                    | •                                |
| Alligator Clips        | •                           |                             | •                                    |                                  |
| Pouch                  | •                           |                             | •                                    |                                  |
| Thermocouple           |                             |                             | K-type                               | K-type                           |
| Warranty               | 2-Year limited              | 1-Year limited              | 2-Year limited                       | 1-Year limited                   |



## Download this competitive comparison here.

Competitive product functionality, features, accessories and pricing are based on public information available at time of publication and subject to change without notice. Competitive brands and images are property of their respective owners.