



# Dual Input Differential Thermometer



## Functions

- Dual input with differential (T1 - T2)
- Temperature range: -328° to 2498°F (-200° to 1370°C)
- Min/Max capture (T1 & T2)

## Features

- Auto power off with disable feature (15 minutes)
- Data hold
- °F/ °C select function
- Magnetic mount
- Large LCD screen with dual readings
- User ice point calibration
- 3-Year limited warranty

## Applications

Measure ambient temperature  
Measure liquid temperatures





### Includes

- K-Type bead probe 2 (ATT29A )
- Battery (9V)
- Manual (17018)
- Pouch

### Specifications

Temperature Range	K-Type: -328°F ~ 2498°F (-200°C ~ 1370°C)
Temperature Unit	C° or F° Selectable
Display Resolution	0.1°C (0.1°F)
Accuracy	±(0.2% + 1.4°F) ±(0.2% + 1°C)
Input Protection	Max voltage of temperature input is 24V DC
Temperature Coefficient	0.01% of reading + 0.03°C per °C 0.01% of reading + 0.06°F per °F When out of range 18°C ~ 28°C (64°F ~ 82°F)
Size	6 1/4" x 2 1/8" x 1 1/2" (H x W x D)

### Downloads



**Manual**



**Data Sheet**

H27-636



Made in TAIWAN