

PowerSpin™ HX Centrifuge

Product Images



Short Description

1. POWERSPIN™ HX CENTRIFUGE
2. FIXED SPEED 3400 RPM
3. 12 PLACE FIXED ANGLE ROTOR
4. 30 MIN. DIGITAL TIMER
5. 6 X10ML CAPACITY
6. POWER INPUT 110V

Description

UNICO PowerSpin™ HXV Series benchtop centrifuges are economical, reliable and super quiet available with horizontal or 12 place fixed angle rotors.

The horizontal rotor insures clean, complete separation of cellular components yielding a superior serum or plasma specimen. Using a horizontal rotor for spinning Serum Separator Tubes (SSTs) creates a tight uniform horizontal seal, reducing the risk of red cell leakage and possibility of specimen deterioration. This is especially important when the specimen is sent out for testing.

The PowerSpin™ HXV features electronically controlled safety lock, so the lid can not be opened while the rotor is in motion. A digital timer and LCD display provide user with the precise control of the spin cycle. Powerful brushless motor is maintenance free for years of dependable use. Stainless steel guard bowl is easy to clean and maintain.

The PowerSpin™ HXV features a Zero RPM safety lock, so the lid cannot be opened while the rotor is in motion. A digital timer and LCD display provide user with the precise control of the spin cycle.

Powerful 100W brushless motor is maintenance free for years of dependable use. Stainless steel guard bowl adds even more protection, and also is easy to clean and maintain.

Additional Information

Accessories	Header	Accessories
	C8300-01	6 place horizontal rotor for HXV C8300 centrifuge
	C8300-02	8 place horizontal rotor for HXV C8300 centrifuge
	C8300-03	12 place angled rotor for HXV C8300 centrifuge
	C800-02	Regular tube shield, pack of 2
	C800-03	Adapter for short tubes, pack of 10
	C800-04	Pediatric or microtube adapter, pack of 2
	C800-05	Tube Lift Adapters, Pk/12
Specification	C800-12	Balance Tube Holdster
	Speed (RPM)	3500
	Maximum RCF (g)	1777g
	Timer	Digital
	Nominal Capacity	12 x 15 ml
	Rotor	Fixed Angle
	Lock	ZERO RPM Digital
	Motor	AC
	Maximum Test Tube Size	16 x 110 mm