

Zoom Stereo Microscope

Product Images



Short Description

- 1. BINOCULAR ZOOM STEREO HEAD
- 2. WF10X PAIRED EYEPIECES
- 3. 0.7X-4.5X CONTINUOUS ZOOM BODY
- 4. FOCUSING STAND WITH TOP AND BOTTOM LED ILLUMINATION

Description

ZM190 Series zoom stereo microscopes adapt multifunction design and excellent manufacturing technology. The ZM190 have been built to meet customer demands for a reliable performance at a competitive price. The superb quality and affordable price make the ZM190 Series ideal instruments for a variety of industrial, medical, educational, and special OEM applications.

Binocular head features high Eyepoint eyepieces, dual diopter control for sharp, clear focus control matched to individual eye differences.

The top and bottom light is a super bright LED designed to provide excellent lighting without giving off heat. Four-way lighting controls: Off, Top light only, Bottom light only, Both Top and bottom light on.

Additional Information

	Header	Bodies
	D4-3001	Binocular Zoom Body 0.7X~4.5X
	D4-3002	Trinocular Zoom Body 0.7X-4.5X
	Header	Eyepieces and Auxiliary Lens
	D4-1001	Widefield Eyepiece 10X FN: 19 mm
	D4-1002	Widefield Eyepiece 15X FN: 14.5 mm
	D4-1003	Widefield Eyepiece 20X FN: 11 mm
	D4-1004	Widefield Eyepiece 25X FN: 9 mm
	D4-1005	Extra Widefield Eyepiece 10X FN: 23 mm
	D4-2001	Auxiliary Lens 2X
	D4-2002	Auxiliary Lens 1.5X
	D4-2003	Auxiliary Lens 0.75X
	D4-2004	Auxiliary Lens 0.5X
	D4-2005	Auxiliary Lens 0.3X
	Header	Stands, Arms and Bases
	D4-4001	PE Stand, pole type with extension pillar
	D4-4001HF	PE-HF Stand, incident halogen (6V, 20W) and transmitted fluorescent illumination (5W)
	D4-4002	DPT Stand, with incident illuminator port
	D4-4003FF	DFF Stand, incident and transmitted fluorescent illumination (5W)
Accessories	D4-4004	DE Stand, two-step extensible arm
	D4-4004HF	Same as D4-4004 but with incident halogen (6V, 20W) and transmitted fluorescent illumination (5W)
	D4-4006	Boom Stand with universal arm (D4-4101 included)
	D4-4007	Boom Stand with 25 mm post carrier (D4-4106 included) and focusing mount (D4-4102 included)
	D4-4101	Universal arm (Bonder Arm) with 5/8 inch knuckle pin
	D4-4102	Focusing mount with 25 mm diameter through hole
	D4-4103	Probe arm
	D4-4104	Boom Stand with 5/8 inch knuckle hole
	D4-4105	Boom Stand with 25 mm post carrier (D4-4106 included)
	D4-4106	25 mm post carrier
	D4-4201	Diascopic base (only use with DPT stand D4-4002)
	Header	Other Components and Accessories
	D4-7002	Fiber optics dual-chrome gooseneck
	D4-7003	Fiber optics ring light
	D4-7004	Fiber optics light source 115V, 100W
	D4-8010	35 mm camera adapter and photo eyepiece system
	D4-8020	video adapter with external C thread, adjustable
	D4-8901	Objective protection ring with glass
	D4-8902	Reticule for 10X eyepiece (D4-1001)
	D4-8903	Reticule for WFH10X eyepiece (D4-1005)
	Head	Ripogular
Specification	Head	Binocular WF10X
	Eyepiece Body	0.7X~4.5X
	Stand	DF-HF Stand
		Dr-нг Stand Top halogen & Bottom fluorescent
	Actual Size	9.7" x 7" x 16.5"
Size and Weight	Shipping Size	
	Net Weight	15.5 lbs (7.0kg)
	Shipping We	ight 17.5 lbs (7.7 kg)